

Remonumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a basalt stone, 14x10x8 ins., firmly set, marked $\frac{1}{4}$ on W. face, from which the original bearing trees:

A fir, 36 ins. diam., bears N. 48° E., 25 lks. dist., marked with portions of scribe marks on open blaze.

A fir, 26 ins., diam., bears S. 82° W., 48 lks. dist., marked with portions of scribed marks on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

$\frac{1}{4}$
S 32 | S 33
T32S R4W
1959

Deposit basalt stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, perpetuated with an iron pipe, 1 in. diam., set by Lawrence and Wright in 1937, from which bearing trees marked in 1937:

A fir, 14 ins. diam., bears S. 61° E., 18 lks. dist., marked with a healed blaze.

A cedar, 14 ins. diam., bears N. 15° W., 61 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

$\frac{1}{4}$
S 20 | S 21
T32S R4W
1959

Reset iron pipe alongside iron post.

The closing cor. of secs. 8 and 9, on the S. bdy. of sec. 5, determined at record bearing and distance from the remaining original bearing tree:

A fir, 40 ins. diam., bears S. 39° W., 36 lks. dist., marked with portions of scribed marks on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

S 5
S 8 | S 9
T32S R4W
C C
1959

FND. OK
11/90 M III-12

from which a new bearing tree

A hemlock, 6 ins. diam., bears S. 40° E., 62 lks. dist., marked T32S R4W S9 CC BT.