

Remonumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. of secs. 29 and 30, determined at record bearing and distance from the remaining original bearing tree:

A fallen fir, 24 ins. diam., bears S. 68° W., 64 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

$\frac{1}{4}$
S 30 | S 29
T32S R4W
1959

from which new bearing trees

A fir, 22 ins. diam., bears S. 88° E., 60 lks. dist., marked $\frac{1}{4}$ S29 BT.

A fir, 36 ins. diam., bears S. 6° W., 90 lks. dist., marked $\frac{1}{4}$ S30 BT.

The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, determined at record bearing and distance from the remaining original bearing tree:

A fir snag, 36 ins. diam., bears S. 47° W., 69 lks. dist., marked with an opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, to top, with brass cap marked

$\frac{1}{4}$ S 20
S 29
T32S R4W
1959

from which new bearing trees

A fir, 13 ins. diam., bears N. 51° E., 49 lks. dist., marked $\frac{1}{4}$ S20 BT.

A fir, 10 ins. diam., bears S. 18° W., 12 lks. dist., marked $\frac{1}{4}$ S29 BT.

(Original corners established by William H. Byars in 1871)

The cor. of secs. 4 and 5, on the N. bdy. of sec. 9, determined at record bearing and distance from each of the remaining original bearing trees:

A yew, 16 ins. diam., bears S. 70° E., 70 lks. dist., marked with portions of scribed marks on open blaze.

A fir, 40 ins. diam., bears N. 45° W., 43 lks. dist., marked S5 T32S R4W BT on bark.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked