

T. 29 S., R. 7 W.

CHAINS

The following record represents a revision of a portions of the east boundary and subdivisional lines of township 29 south, range 7 west, of the resurvey executed in 1957, under Group No. 346. The original survey was executed by Nathaniel Ford in 1854; the resurvey was executed by Hans W. Thielsen, Cadastral Surveyor, in 1957.

Examination of the County Records shows the  $\frac{1}{4}$  section corner of sections 7 and 12, on the east boundary of the township, to have been perpetuated by James Byram, Deputy County Surveyor, in 1957, at record bearing and distance from the remaining original bearing trees.

The corner position of the  $\frac{1}{4}$  section corner of sections 7 and 12 was adjusted to conform to the original and the County Surveyor's record. Other lost corners in the township, dependent on the  $\frac{1}{4}$  section corner of sections 7 and 12 as control, were adjusted and iron posts moved to conform with original positions. The method of procedure of this revision survey is as described in the preliminary statement of the official record of the 1957 resurvey.

Dependent Resurvey of a Portion of the E. Bdy., T. 29 S., R. 7 W., Will. Mer., Oregon.  
(Restoring the 1854 survey by Nathaniel Ford.)

From the cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., extending 8 ins. above ground, firmly set, with brass cap marked and witnessed as described in the official record.


N. 1° 59' W., bet. secs. 13 and 18, marking and blazing the true line.

Descend 310 ft. over N. slope, through heavy timber and dense undergrowth.

9.40 Porter Creek, 5 lks. wide, course N. 80° E.; asc. 690 ft. over SE. slope.

38.31 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which

A fir, 17 ins. diam., bears S. 89° E., 95 lks. dist., marked  $\frac{1}{4}$  S 18 BT.

A fir, 12 ins. diam., bears N. 19° W., 81 lks. dist., marked  $\frac{1}{4}$  S 13 BT.

Ascend 170 ft. over SE. slope.

46.70 Ridge, bears NE. and SW.; desc. 800 ft. over NW. slope.

76.62 Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.