

Dependent Resurvey of a Portion of the E. Bdy., T. 29 S., R. 7 W.

CHAINS

Set and iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T29S	
R7W	R6W
S 12	S 7
S 13	S 18
1957	

from which

A maple, 10 ins. diam., bears N. 80° E., 109 lks. dist., marked T29S R6W S7 BT.

A maple, 12 ins., diam., bears S. 43½° E., 135 lks. dist., marked T29S R6W S18 BT.

A fir, 16 ins. diam., bears S, 77° W., 142 lks. dist., marked T29S R7W S13 BT.

A fir, 10 ins. diam., bears N. 61° W., 348 lks. dist., marked T29S R7W S 12 BT.

The corner falls in a ravine, drains NW.

Land, mountainous. Soil, rocky clay. Timber, fir, cedar, madrone, maple and alder; undergrowth, vine maple, hazel, arrowwood, Oregon grape and fern.

N. 1° 59' W., bet. secs. 7 and 12.

Ascend 60 ft. over SW. slope, through heavy timber and dense undergrowth.

7.70 Spur, slopes W.; desc. 275 ft. over NW. slope.

19.155 Point for the S 1/16 sec. cor. of secs. 7 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

S 1/16	
S 12	S 7
R7W	R6W
T29S	
1958	

from which

A fir, 14 ins. diam., bears N. 40½° E., 268 lks. dist., marked S 1/16 S7 BT.

A fir, 14 ins. diam., bears N. 9° W., 221 lks. dist., marked S 1/16 S12 BT.

Descend 25 ft. over NW. slope.

21.25 Kent Creek, 6 lks. wide, course NE.; asc. 330 ft. over SE. slope.

23.15 Kent Creek Road, 30 lks. wide, bears N. 30° E. and S. 30° W.

38.31 The ¼ sec. cor. of secs. 7 and 12, perpetuated and recorded by the County Surveyor from the original bearings trees, monumented with an iron post, 1 in. diam., extending 8 ins. above ground, firmly set, with brass cap marked

County Surveyors Office

T29S

R	R
7 ½	S 12 7 6