

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 29 S., R. 7 W.

CHAINS

- 53.40 Ravine, drains S. 70° E.; asc. 540 ft. over SE. slope.
- 73.50 Ridge, bears E. and W.; desc. 140 ft. over NE. slope.
- 78.68 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T29S R7W
 S 11 | S 12
 S 14 | S 13
 1957

from which

- A fir, 9 ins. diam., bears N. 51° E., 200 lks. dist., marked T29S R7W S12 BT.
- A fir, 9 ins. diam., bears S. 44° E., 110 lks. dist., marked T29S R7W S13 BT.
- A fir, 8 ins. diam., bears S. 15° W., 74 lks. dist., marked T29S R7W S14 BT.
- A fir, 11 ins. diam., bears N. 66½° W., 61 lks. dist., marked T29S R7W S11 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, cedar, maple, chinquapin, madrone and alder; undergrowth, vine maple, arrow-wood, Oregon grape and fern.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp. N. 86° 35' W., bet. secs. 12 and 13.

Descend 10 ft. over broken N. slope, through heavy timber and dense undergrowth.

- 4.10 Stream, 3 lks. wide, course N.; asc. 30 ft. over NE. slope.
- 7.50 Spur, slopes N.; desc. 220 ft. over broken NW. slope.
- 18.50 Gravelled road, 20 lks. wide, bears N. and S. 30° W.
- 20.50 Kent Creek, 10 lks. wide, course N. 30° E.; asc. 610 ft. over E. slope.
- 43.03 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

T29S R7W
 ¼ S 12
 ¼ S 13
 1957

from which

- A fir, 6 ins. diam., bears N. 11° E., 118 lks. dist., marked ¼ S12 BT.
- A fir, 14 ins. diam., bears S. 20° E., 84 lks. dist., marked ¼ S13 BT.