

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 29 S., R. 7 W.

## CHAINS

Ascend slightly over NE. slope, through heavy timber and dense undergrowth.

- 0.15 Spur, slopes N. 15° E.; desc. 180 ft. over broken NW. slope.
- 12.75 Ravine, drains N. 20° E.; asc. 200 ft. over NE. slope.
- 18.60 Ridge, bears N. and S.; desc. 590 ft. over NW. slope.
- 34.45 Branch, 3 lks. wide, course N. 50° W.; asc. 50 ft. over NE. slope.
- 39.35 Spur, slopes N. 20° W.; desc. 90 ft. over NW. slope.
- 42.955 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

FIND OK  
A/91 M113.6

T29S R7W

S 11

$\frac{1}{4}$  S 14

1957

from which

A fir, 14 ins. diam., bears N. 6 $\frac{1}{2}$ ° E., 6 lks. dist., marked  $\frac{1}{4}$  S11 BT.

A fir, 8 ins. diam., bears South, 70 lks. dist., marked  $\frac{1}{4}$  S14 BT.

Descend 10 ft. over NW. slope.

- 43.75 McNabb Creek, 5 lks. wide, course N.; asc. 480 ft. over E. slope.
- 58.95 Spur ridge, bears N. 25° E. and S. 25° W.; desc. 300 ft. over NW. slope.
- 71.35 Branch, 3 lks. wide, course N. 20° E.; asc. 200 ft. over E. slope.
- 80.35 Ridge, bears N. 20° E. and S.; desc. 160 ft. over NW. slope.
- 85.91 The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., extending 8 ins. above ground, firmly set, with brass cap marked and witnessed as described in the official record.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, maple, madrone and alder; undergrowth, vine maple, hazel, arrowwood, poison oak and fern.

## General Description

The general description of this area is as described in the official record of the 1957 resurvey.