

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of S. Bdy. of T. 29 S., R. 6 W.

CHAINS

T 29 S R 6 W
 S 33 | S 34
 S 4 | S 3
 T 30 S
 1958

2/22/78
 SEE LETTER
 ATTACHED TO
 NOTES in
 C.S. #7/93

from which bearing trees not of record, found by Byron in 1956:

A fir, 50 ins. diam., bears N. $4\frac{1}{4}^\circ$ W., 54 lks. dist.,
 mkd. with an open blaze and parts of scribe marks.

A fir snag, 40 ins. diam., bears S. 9° E., 21 lks. dist.,
 mkd. with an open blaze and parts of scribe marks.

and bearing trees marked by Byron in 1956:

A fir, 26 ins. diam., bears N. 62° E., $130\frac{1}{2}$ lks. dist.,
 mkd. T29S R6W S34 CS BT.

A fir, 18 ins. diam., bears S. 57° E., 59 lks. dist.,
 mkd. T29S R6W S3 CS BT.

A fir, 4 ins. diam., bears S. $58\frac{1}{4}^\circ$ W., 28 lks. dist.,
 mkd. S4 CS BT.

A fir, 12 ins. diam., bears N. $20\frac{1}{2}^\circ$ W., $93\frac{1}{2}$ lks. dist.,
 mkd. T29S R6W S33 CS BT.

I correct the marks on the SE. tree to read T30S R6W S3 CS BT and
 bury the County Surveyor's monument alongside the iron post.

N. $89^\circ 24'$ W., on the N. bdy. of sec. 4, T. 30 S., R. 6 W., marking
 and blazing the true line.

Ascend 5 ft. over broken NE. slope, through fir timber.

7.65 Stream, 1 lk. wide, 2 ins. deep, course N.; asc. 195 ft. over
 broken NE. slope.

30.40 Spur, slopes N.; desc. 90 ft. over NW. slope.

37.30 Draw, drains N.; asc. 25 ft. over NE. slope.

38.60 Point for the $\frac{1}{4}$ sec. cor. of sec. 33, T. 29 S., R. 6 W., hereinafter
 described.

Ascend 45 ft. over NE. slope.

44.16 Point for the $\frac{1}{4}$ sec. cor. of sec. 4, at proportionate distance;
 there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
 ground, with brass cap mkd.

$\frac{1}{4}$ S 4
 T 30 S R 6 W
 1958

from which

A fir, 8 ins. diam., bears S. 3° E., 70 lks. dist.,
 mkd. $\frac{1}{4}$ S4 BT.

A fir, 8 ins. diam., bears S. 57° W., 55 lks. dist.,
 mkd. $\frac{1}{4}$ S4 BT.