

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of S. Bdy. of T. 29 S., R. 6 W.

CHAINS

from which

A cedar, 16 ins. diam., bears S. 28° E., 216 lks. dist.,
mkd. E 1/16 S5 BT.

A cedar, 11 ins. diam., bears S. 33° W., 212 lks. dist.,
mkd. E 1/16 S5 BT.

Continue along S. slope.

20.90 Dirt road, bears N. 30° E. and S. 30° W.; enter along woven wire
fence; asc. 110 ft. over SE. slope.

25.10 Spur, slopes S. from Big Baldy Mountain; desc. 15 ft. over NW.
slope.

27.16 Point for the $\frac{1}{4}$ sec. cor. of sec. 32 only, at midpoint in departure
on the S. bdy. of sec. 32.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap mkd.

$\frac{1}{4}$ S 32
T 29 S R 6 W
1958

from which

An oak, 30 ins. diam., bears N. 83° W., 114 lks. dist.,
mkd. $\frac{1}{4}$ S32 BT.

Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Descend 90 ft. over NW. slope, through scattered fir and oak timber.

37.00 Wet draw, drains SW.; asc. 22 ft. over SE. slope.

38.16 The $\frac{1}{4}$ sec. cor. of sec. 5, T. 30 S., R. 6 W., monumented with a
slate stone, 14x10x6 ins., set in a small mound of stone, mkd. $\frac{1}{4}$ on
N. face, from which the remains of trees marked by Mensch in 1904:

An oak, 9 ins. diam., dead and fallen, bears S. 40° W.,
42 lks. dist., mkd. $\frac{1}{4}$ S on open blaze.

An oak, dead, fallen and rotted, bears N. 46° W., 13 lks.
dist., no marks remain.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the
ground, to solid rock, and in a mound of stone, 5 ft. base, to top,
with brass cap mkd.

$\frac{1}{4}$ S 5
T 30 S R 6 W
1958

from which new bearing trees:

A cedar, 15 ins. diam., bears S. $51\frac{1}{2}$ ° E., 50 lks. dist.,
mkd. $\frac{1}{4}$ S5 BT.

A fir, 12 ins. diam., bears S. 31° W., 37 lks. dist.,
mkd. $\frac{1}{4}$ S5 BT.

Bury original stone alongside the iron post.