

## County Surveyor's Record, Douglas County, Oregon

## Dependent Resurvey of Portion of S. Bdy. of T. 29 S., R. 6 W.

## CHAINS

from which new bearing trees:

A fir, 16 ins. diam., bears S.  $43\frac{3}{4}^{\circ}$  E., 102 lks. dist.,  
mkd. T30S R6W S5 BT.

A fir, 23 ins. diam., bears S.  $23^{\circ}$  W., 95 lks. dist.,  
mkd. T30S R6W S6 BT.

Bury original corner stone alongside the iron post.

Land, mountainous.

Soil, rocky clay loam in the draws along the W. half.

Timber, fir, cedar, oak, madrona, yew, and scattered pine.

Undergrowth, young timber, blackberry, poison oak, vines and ferns.

Dependent Resurvey of Portion of the Subdivisional Lines of  
T. 29 S., R. 6 W.

(Restoring the surveys executed by Nathaniel Ford, in 1854;  
William Byars, in 1872; H. G. Hurlburt, in 1878;  
and retracements by Fred Mensch, in 1904)

From the cor. of secs. 26, 27, 34, and 35, perpetuated with an iron pipe, 1 in. diam., 8 ins. above ground, firmly set. This cor. was first established by Ford, in 1854, reestablished by Byars, in 1872. The Douglas County records show that Roberts, Deputy County Surveyor renewed the cor., in 1903, with new bearing trees. John Markham, C. E., renewed the cor., in 1951, with the above described iron pipe and marked two new bearing trees.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T 29 S R 6 W  
S 27 | S 26  
S 34 | S 35  
1958

from which trees marked by Roberts in 1903:

A fir, 24 ins. diam., bears S.  $53\frac{1}{2}^{\circ}$  E., 84 lks. dist.,  
mkd. with healed blaze.

A fir, 28 ins. diam., dead and fallen, bears S.  $79\frac{1}{4}^{\circ}$  W.,  
62 lks. dist., mkd. with healed blaze.

A fir, 22 ins. diam., dead and fallen, bears N.  $59\frac{1}{2}^{\circ}$  W.,  
 $48\frac{1}{2}$  lks. dist., mkd. with healed blaze.

and trees marked by Markham in 1951:

A fir, 9 ins. diam., bears S.  $6^{\circ}$  E., 22 lks. dist.,  
mkd. with healed blaze.

A fir, 44 ins. diam., bears N.  $10^{\circ}$  W.,  $48\frac{1}{2}$  lks. dist.,  
mkd. with healed blaze.

and new bearing trees:

A fir, 24 ins. diam., bears N.  $69^{\circ}$  E.,  $76\frac{1}{2}$  lks. dist.,  
mkd. T29S R6W S26 BT.

A fir, 7 ins. diam., bears S.  $32\frac{1}{4}^{\circ}$  W.,  $32\frac{1}{2}$  lks. dist.,  
mkd. BT only, at base.