

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

<p>CHAINS 36.72</p> <p>* Per research I believe that the renewal attributed to Boyer was actually done by John Markham see previous renewal system ren # 71 2-23-2011 DCSOJC</p>	<p>The cor. of secs. 22, 23, 26, and 27, perpetuated with an iron pipe, 1 in. diam., 6 ins. above ground, firmly set. This cor. was established by Ford, in 1854. The Douglas County records show that Arthur Boyer, Deputy County Surveyor, remonumented the cor. with the iron pipe and marked new bearing trees, in 1941. Boyer states that the cor. was determined from original bearing trees marked by Ford.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 6 W</p> <table border="1"> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table> <p>1958</p> </div> <p>from which trees marked by Boyer in 1941:</p> <p>A fir, 35 ins. diam., bears S. 46° E., 23½ lks. dist., mkd. S BT.</p> <p>A fir, 31 ins. diam., bears S. 16½° W., 16 lks. dist., mkd. S27 CS BT.</p> <p>A fir, 12 ins. diam., bears N. 57½° W., 30 lks. dist., mkd. BT on partly open blaze.</p> <p>and new bearing trees:</p> <p>A fir, 15 ins. diam., bears N. 13¼° E., 29 lks. dist., mkd. T29S R6W S23 BT.</p> <p>A fir, 35 ins. diam., bears S. 46° E., 23½ lks. dist., mkd. T29S R6W S26 BT.</p> <p>A fir, 31 ins. diam., bears S. 16½° W., 16 lks. dist., mkd. T29S R6W S27 BT.</p> <p>A fir, 12 ins. diam., bears N. 57½° W., 30 lks. dist., mkd. T29S R6W S22 BT.</p> <p>Bury the iron pipe alongside the iron post.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, madrona, maple, oak and alder. Undergrowth, young timber, vinemaple, poison oak, arrowwood, ferns and vines.</p> <hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp. N. 1°04' E., bet. secs. 33 and 34.</p> <p>Descend 90 ft. over NE. slope, through heavy fir, maple and madrona timber.</p> <p>8.00 Draw, drains NW.; asc. 15 ft. over SW. slope.</p> <p>10.20 Spur, slopes W.; desc. slightly along broken W. slope.</p> <p>36.80 Spur, slopes N. 20° W.; desc. 115 ft. over N. slope.</p> <p>40.98 The ¼ sec. cor. of secs. 33 and 34, determined at record bearing and distance from the original NW. bearing tree:</p>	S 22	S 23	S 27	S 26
S 22	S 23				
S 27	S 26				