

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS

A fir, 40 ins. diam., bears N. 30° W., 17 lks. dist.,
mkd. $\frac{1}{4}$ S on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap mkd.

$\frac{1}{4}$
S 33 | S 34
T 29 S | R 6 W
1958

from which new bearing trees:

A fir, 45 ins. diam., bears S. 53° E., 70 lks. dist.,
mkd. $\frac{1}{4}$ S34 BT.

A fir, 37 ins. diam., bears S. 57° W., 51 lks. dist.,
mkd. $\frac{1}{4}$ S33 BT.

N. 0° 16' W., beginning new measurement.

Descend 220 ft. over N. slope.

7.40 Wet draw, drains NW.; asc. 10 ft. over SW. slope.

8.50 Spur, slopes W.; desc. 250 ft. over broken NW. slope.

29.70 Top of cliff, 50 ft. high, bears E. and W.; desc. 235 ft. over
cliff and N. slope, to sec. cor.

39.50 Stream, 5 lks. wide, 6 ins. deep, course NW.

40.34 The cor. of secs. 27, 28, 33, and 34, determined at record bearing
and distance from the remaining original bearing tree and bearing
trees marked by S. W. Cole, Deputy County Surveyor, in 1924, and
recorded in the Douglas County records, from which the original
bearing tree:

A cedar, 30 ins. diam., dead and fallen, bears N. 40° W.,
37 lks. dist., mkd. 8 in open blaze.

and trees marked by Cole in 1924:

A cedar, 45 ins. diam., bears N. 35 $\frac{1}{2}$ ° E., 74 lks. dist.,
mkd. CS on partly open blaze.

A fir, 16 ins. diam., bears S. 46 $\frac{3}{4}$ ° W., 42 lks. dist.,
mkd. with healed blaze. Reblaze and mark T29S R6W S34 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the
ground, to solid rock, and in a mound of stone, 8 ft. base, to top,
with brass cap mkd.

T 29 S R 6 W
S 28 | S 27
S 33 | S 34
1958

from which new bearing trees:

A fir, 19 ins. diam., bears S. 76° E., 38 lks. dist.,
mkd. T29S R6W S34 BT.