

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS	
	From the cor. of secs. 27, 28, 33, and 34. N. 89°34' W., bet. secs. 28 and 33.
0.05	Stream, 5 lks. wide, 6 ins. deep, course NW.; asc. 35 ft. over broken NE. slope, through heavy fir, cedar, maple and madrona timber.
13.20	Spur, slopes NW.; desc. 165 ft. over SW. slope.
25.90	Stream, 5 lks. wide, 4 ins. deep, course NW.; asc. 135 ft. over NE. slope.
39.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.  $\begin{array}{c} \frac{1}{4} S 28 \\ \frac{1}{4} S 33 \\ T 29 S R 6 W \\ 1958 \end{array}$ from which  A pine, 30 ins. diam., bears N. 37° E., 29 lks. dist., mkd. $\frac{1}{4}$ S28 BT.  A madrona, 8 ins. diam., bears South, 10 lks. dist., mkd. $\frac{1}{4}$ S33 BT.  Ascend 40 ft. over NE. slope.
42.80	Spur, slopes N.; desc. 180 ft. over NW. slope.
48.65	Stream, 8 lks. wide, 6 ins. deep, course N. 20° E.; asc. 130 ft. over NE. slope.
56.80	Spring branch, 1 lk. wide, flows NE.; asc. 110 ft. over NE. slope.
65.20	Point of spur, slopes NE.; asc. 175 ft. over SE. slope.
73.30	Spur, slopes NE.; desc. 15 ft. over NW. slope.
75.40	Spring branch, 1 lk. wide, flows NE.; asc. 55 ft. over SE. slope.
78.02	The cor. of secs. 28, 29, 32, and 33, monumented with a limestone, 15x12x10 ins., loosely set in a small mound of stone, mkd. with 1 notch on S. and 4 notches on E. edges. This cor. was established by Hurlburt, in 1878. In 1904, Mensch remonumented the cor. with the described limestone and marked new bearing trees. The remaining Mensch bearing trees are as follows:  A madrona, 24 ins. diam., bears N. 25° E., 44 lks. dist., mkd. T29S R6W S28 BT. This tree is partly dead.  A madrona, 24 ins. diam., partly dead and rotted, bears S. 26° E., 44 lks. dist., mkd. T29S R6 on decayed blaze.  A chinquapin, 16 ins. diam., bears N. 44° W., 53 lks. dist., mkd. T29S R6W S29 BT.  At the corner point  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.