

County Surveyor's Record, Douglas County, Oregon

15

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS

T 29 S R 6 W
 S 29 | S 28
 S 32 | S 33
 1958

from which new bearing trees:

A cedar, 24 ins. diam., bears N. 75° E., 62 lks. dist.,
 mkd. T29S R6W S28 BT.

A fir, 25 ins. diam., bears S. 16° E., 97 lks. dist.,
 mkd. T29S R6W S33 BT.

A fir, 32 ins. diam., bears N. 37½° W., 47 lks. dist.,
 mkd. T29S R6W S29 BT.

The area to the SW. of this cor. is extensively logged and no suitable bearing tree is available. Bury the limestone alongside the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, madrona, oak, maple and chinquapin.

Undergrowth, young timber, vinemaple, poison oak, vines and ferns.

S. 0°06' E., bet. secs. 32 and 33.

Descend 30 ft. over SE. slope, through medium timber.

- 3.50 Spring branch, 1 lk. wide, flows NE.; asc. 525 ft. over NE. slope.
- 29.40 Spur, slopes E.; desc. 115 ft. over SE. slope.
- 39.87 Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

¼
 S 32 | S 33
 T 29 S | R 6 W
 1958

from which

A fir, 47 ins. diam., bears S. 32° E., 38 lks. dist.,
 mkd. ¼ S33 BT.

A fir, 30 ins. diam., bears N. 37° W., 52 lks. dist.,
 mkd. ¼ S32 BT.

Ascend 130 ft. over N. slope.

- 43.30 Spur, slopes E.; desc. 220 ft. over SE. slope.
- 48.70 Stream, 1 lk. wide, course E.; asc. 295 ft. over NW. slope.
- 56.70 Spur, slopes NE.; desc. 120 ft. over SW. slope.
- 65.50 Stream, 1 lk. wide, course SE.; asc. 18 ft. over NE. slope.
- 66.80 Spur, slopes E.; desc. 32 ft. over SE. slope.
- 68.60 Stream, 1 lk. wide, course E.; asc. 165 ft. over NE. slope.