

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS

80.90

Stream, 1 lk. wide, course NE.

80.99

The original closing cor. of secs. 32 and 33, determined at record bearing and distance from the remaining original bearing tree:

A fir, 25 ins. diam., partially dead, bears N. 43° E.,
31 lks. dist., mkd. S R6W S33 BT.

81.20

Intersect the S. bdy. of the Tp.

Point for the closing cor. of secs. 32 and 33.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

C C
T 29 S | R 6 W
S 32 | S 33
S 4
T 30 S R 6 W
1958

from which

A fir, 10 ins. diam., bears N. 58° E., 146 lks. dist.,
mkd. T29S R6W S33 CC BT.

A cedar, 10 ins. diam., bears N. 22½° W., 378 lks. dist.,
mkd. T29S R6W S32 CC BT.

From this point the cor. of secs. 4 and 5, T. 30 S., R. 6 W., bears N. 89°24' W., 11.12 chs. dist.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrona, chinquapin and alder.

Undergrowth, young timber, poison oak, arrowwood, hazel and ferns.

To complete the survey of sec. 33, I return to the ¼ sec. cor. of sec. 4, on the N. bdy. of sec. 4, T. 30 S., R. 6 W., and run

S. 89°24' E., on the S. bdy. of sec. 33.

5.56

Point for the ¼ sec. cor. of sec. 33 only, at midpoint on the S. bdy. of sec. 33.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

¼ S 33
T 29 S R 6 W
1958

from which

A fir, 9 ins. diam., bears N. 38½° E., 56 lks. dist.,
mkd. ¼ S33 BT.

A fir, 10 ins. diam., bears N. 27° W., 47 lks. dist.,
mkd. ¼ S33 BT.

From the ¼ sec. cor. of secs. 20 and 21, perpetuated with a car axle, driven firmly in the ground. The Douglas County records show that this axle was set by Ben Irving, Deputy County Surveyor, in 1929, from remaining evidence of the original bearing trees,