

## Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

## CHAINS

From the  $\frac{1}{4}$  sec. cor. of secs. 16 and 21, perpetuated with an automobile drive shaft, firmly driven in the ground, and in a mound of stone, 2 ft. base, 1 ft. high. The Douglas County records show that S. W. Cole, County Surveyor, raised the mound of stone, in 1923, determining the position from the original SW. bearing tree, marked by Ford, in 1854. In 1929, the drive shaft was driven at the corner point, and additional bearing trees were marked in 1954.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S 16  
 $\frac{1}{4}$  S 21  
T 29 S R 6 W  
1958.

from which the remains of the original bearing tree:

A sawed oak stump, 24 ins. diam., bears S.  $11^{\circ}$  W., 169 lks. dist., no marks remain.

and bearing trees marked by the County Surveyor in 1954:

A cedar, 14 ins. diam., bears N.  $37^{\circ}$  W., 32 lks. dist., mkd.  $\frac{1}{4}$  S16 CS BT.

A cedar, 14 ins. diam., bears S.  $5^{\circ}$  W., 15 lks. dist., mkd.  $\frac{1}{4}$  S21 CS BT.

and new bearing trees:

A fir, 9 ins. diam., bears N.  $64\frac{1}{4}^{\circ}$  W., 28 lks. dist., mkd.  $\frac{1}{4}$  S16 BT.

A cedar, 20 ins. diam., bears S.  $28^{\circ}$  E., 89 lks. dist., mkd.  $\frac{1}{4}$  S21 BT.

Bury the drive shaft alongside the iron post.

N.  $88^{\circ}03'$  W., bet. secs. 16 and 21.

Descend 75 ft. over SW. slope, through medium fir, cedar, madrona and oak timber.

- 5.70 West Willis Creek Road, 35 lks. wide, bears NE. and SW.; desc. 25 ft. over SW. slope.
- 12.60 West Willis Creek, 10 lks. wide, 6 ins. deep, course NE.; asc. 310 ft. over SE. slope, to sec. cor.
- 16.20 Logging road, 10 lks. wide, bears NE. and SW.
- 39.78 The cor. of secs. 16, 17, 20, and 21.
- 
- N.  $1^{\circ}05'$  E., bet. secs. 16 and 17.
- Ascend 150 ft. over SE. slope, through medium fir, pine, madrona, cedar and oak timber.
- 8.30 Spur, slopes S.  $60^{\circ}$  E., desc. 75 ft. over NE. slope.
- 16.90 Draw, drains E.; asc. 10 ft. over SE. slope.
- 19.19 Point for the S  $1/16$  sec. cor. of secs. 16 and 17.