

## County Surveyor's Record, Douglas County, Oregon

19

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap mkd.

S 1/16  
S 17 | S 16  
T 29 S | R 6 W  
1958

from which

A fir, 15 ins. diam., bears S.  $54^{\circ}$  E., 51 lks. dist., mkd. S 1/16 S16 BT.

A fir, 12 ins. diam., bears S.  $23\frac{1}{2}^{\circ}$  W., 36 lks. dist., mkd. S 1/16 S17 BT.

Ascend 180 ft. over SE. slope.

30.90 Spur, slopes E.; desc. 70 ft. over NE. slope.

38.38 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

S 17 | S 16  
T 29 S | R 6 W  
1958

from which

A fir, 5 ins. diam., bears N.  $75\frac{1}{2}^{\circ}$  E., 58 lks. dist., mkd.  $\frac{1}{4}$  S16 BT.

A fir, 14 ins. diam., bears S.  $57\frac{1}{4}^{\circ}$  W., 80 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

Descend 20 ft. over NE. slope.

41.30 Draw, drains S.  $60^{\circ}$  E.; asc. 230 ft. over SE. slope.

53.10 Ridge and logging road, bears NE. and SW.; desc. 65 ft. over NW. slope.

56.20 Head of draw, drains W.; asc. 35 ft. over SW. slope.

57.57 Point for the N 1/16 sec. cor. of secs. 16 and 17.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16  
S 17 | S 16  
T 29 S | R 6 W  
1958

from which

A fir, 14 ins. diam., bears N.  $73\frac{1}{2}^{\circ}$  E., 77 lks. dist., mkd. N 1/16 S16 BT.

A fir, 15 ins. diam., bears N.  $22^{\circ}$  W., 104 lks. dist., mkd. N 1/16 S17 BT.

Ascend 125 ft. over SW. slope.