

County Surveyor's Record, Douglas County, Oregon

21

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS

T 29 S R 6 W
 S 19 | S 20
 S 30 | S 29
 1958

FD OK PER JOHNSTONE
 m 101-73 12/89

from which new bearing trees:

A fir, 10 ins. diam., bears N. 22 3/4° E., 37 lks. dist.,
 mkd. T29S R6W S20 BT.

A fir, 12 ins. diam., bears N. 22 1/2° W., 91 lks. dist.,
 mkd. T29S R6W S19 BT.

N. 1°33' W., bet. secs. 19 and 20.

Descend 100 ft. over NW. slope, over open land, no timber.

- 5.10 Draw, drains W.; enter scattering timber, edge bears E. and W.;
 asc. 190 ft. over SW. slope.
- 11.10 Spur, slopes W.; desc. 140 ft. over NW. slope.
- 16.00 Draw, drains W.; asc. 65 ft. over SW. slope, to S 1/16 sec. cor.
- 19.42 Woven wire fence, bears E. and W.
- 19.58 Point for the S 1/16 sec. cor. of secs. 19 and 20.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the
 ground, with brass cap mkd.

S 1/16
 S 19 | S 20
 T 29 S | R 6 W
 1958

from which

A fir, 7 ins. diam., bears S. 47° E., 15 lks. dist.,
 mkd. S 1/16 S20 BT.

A fir, 10 ins. diam., bears N. 61° W., 4 lks. dist.,
 mkd. S 1/16 S19 BT.

Ascend 85 ft. over SW. slope.

- 26.90 Spur, slopes W.; desc. 325 ft. over NE. slope.
- 36.60 Draw, drains W.; asc. 40 ft. over SW. slope.
- 39.16 Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate
 distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the
 ground, with brass cap mkd.

1/4
 S 19 | S 20
 T 29 S | R 6 W
 1958

from which

A fir, 30 ins. diam., bears S. 81° E., 3 lks. dist.,
 mkd. 1/4 S20 BT.