

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, pine, oak, maple, madrona, cedar, cottonwood and alder.
Undergrowth, young timber, poison oak, arrowwood, hazel, berry,
vines, ferns and grass.

From the cor. of secs. 16, 17, 20, and 21.

N. 88°59' W., bet. secs. 17 and 20.

Ascend 330 ft. over SE. slope, through medium timber.

19.20 Ridge, bears N. and S.; desc. 420 ft. over SW. slope.

39.77 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 17
 $\frac{1}{4}$ S 20
T 29 S R 6 W
1958

from which

A fir, 20 ins. diam., bears N. 9° W., 68 lks. dist.,
mkd. $\frac{1}{4}$ S17 BT.

A fir, 16 ins. diam., bears S. 59° W., 192 lks. dist.,
mkd. $\frac{1}{4}$ S20 BT.

Descend 150 ft. over SW. slope.

50.92 Stream, 1 lk. wide, course N. 40° W.; asc. 40 ft. over NE. slope.

54.60 Spur, slopes N.; desc. 70 ft. over NW. slope, to W 1/16 sec. cor.

58.10 Dirt road, 15 lks. wide, bears N. and S.; enter open land.

59.655 Point for the W 1/16 sec. cor. of secs. 17 and 20.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{1}{4}$ S 17
 $\frac{1}{4}$ S 20
T 29 S R 6 W
1958

from which

An oak, 12 ins. diam., bears N. 84° E., 164 lks. dist.,
mkd. W 1/16 S17 BT.

A fir, 5 ins. diam., bears S. 27 $\frac{3}{4}$ ° E., 195 lks. dist.,
mkd. W 1/16 S20 BT.

Descend 15 ft. over NW. slope, through open field.

62.60 Rice Creek, 6 lks. wide, 8 ins. deep, course N. to NE.; asc. 30 ft. over E. slope.

71.00 Rice Creek Road, 30 lks. wide, bears NE. and SW.; asc. 180 ft. over SE. slope.