

## County Surveyor's Record, Douglas County, Oregon

25

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

## CHAINS

81.11 The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, maple, madrona and chinquapin.

Undergrowth, young timber, poison oak, hazel, arrowwood, ferns, berry and vines.

From the cor. of secs. 17, 18, 19, and 20.

N. 3°17' E., bet. secs. 17 and 18.

Ascend 50 ft. over SE. slope, through medium timber.

2.40 Spur, slopes E.; desc. 160 ft. over NE. slope.

11.00 Draw, drains SE.; asc. 60 ft. over SW. slope, to S 1/16 sec. cor.

11.85 Dirt road, 10 lks. wide, bears NW. and SE.

19.605 Point for the S 1/16 sec. cor. of secs. 17 and 18.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

S 1/16  
S 18 | S 17  
T 29 S | R 6 W  
1958

from which

A fir, 15 ins. diam., bears N. 57° E., 128 lks. dist., mkd. S 1/16 S17 BT.

A fir, 8 ins. diam., bears S. 89° W., 204 lks. dist., mkd. S 1/16 S18 BT.

Ascend 160 ft. over S. slope, up an open draw.

32.10 Spur, in saddle, slopes E. from ridge; desc. 30 ft. over NE. slope, through medium timber.

34.70 Head of draw, drains NE.; asc. 30 ft. over SE. slope.

39.21 The  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, determined at record bearing and distance from the remaining original bearing tree:

A madrona, 30 ins. diam., bears S. 6 $\frac{1}{2}$ ° W., 44 lks. dist., mkd.  $\frac{1}{4}$  S BT on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
S 18 | S 17  
T 29 S | R 6 W  
1958

from which new bearing trees:

A fir, 14 ins. diam., bears S. 24 $\frac{1}{4}$ ° E., 44 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.