

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS

A fir, 12 ins. diam., bears N. 50° W., 59 lks. dist.,
mkd. $\frac{1}{4}$ S18 BT.

N. 2°33' E., beginning new measurement.

0.10 Spur, slopes E.; desc. 90 ft. over NE. slope.

5.00 Draw, drains E.; asc. 310 ft. over S. slope.

18.89 Point for the N 1/16 sec. cor. of secs. 17 and 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

*Renewed
D Edworts
1-4-2012
CS 65/76-4
from which*

N 1/16
S 18 | S 17
T 29 S | R 6 W
1958

A fir, 13 ins. diam., bears N. 82° E., 11 lks. dist.,
mkd. N 1/16 S17 BT.

A fir, 10 ins. diam., bears S. 51° W., 25 lks. dist.,
mkd. N 1/16 S18 BT.

Ascend 10 ft. over S. slope.

19.40 Ridge, bears N. 65° E. and SW.; desc. 400 ft. over N. slope, changing to NW.

31.00 Draw, drains NE.; asc. 35 ft. over SW. slope.

35.20 Spur, slopes W.; desc. 90 ft. over NW. slope.

37.78 The cor. of secs. 7, 8, 17, and 18, determined at record bearing and distance from the remaining original bearing tree:

A madrona, 30 ins. diam., bears S. 17° W., 16 lks. dist.,
mkd. BT on bark, with open and rotted blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 29 S R 6 W
S 7 | S 8
S 18 | S 17
1958

*FD. OK 4/83
E. Bloom
C.S. 58/242*

from which new bearing trees:

A fir, 10 ins. diam., bears N. 12° E., 82 lks. dist.,
mkd. T29S R6W S8 BT.

A fir, 8 ins. diam., bears S. 66° E., 100 lks. dist.,
mkd. T29S R6W S17 BT.

A fir, 12 ins. diam., bears S. 78° W., 50 lks. dist.,
mkd. T29S R6W S18 BT.

A fir, 8 ins. diam., bears N. 83° W., 84 lks. dist.,
mkd. T29S R6W S7 BT.