

## County Surveyor's Record, Douglas County, Oregon

27

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

## CHAINS

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, pine, cedar, oak, madrona, and chinquapin.  
Undergrowth, young timber, poison oak, hazel, arrowwood, berry,  
vines and ferns.

From the cor. of secs. 8, 9, 16, and 17.

N. 88°05' W., bet. secs. 8 and 17.

Descend 565 ft. over NW. slope, through medium timber, to Rice  
Creek.

25.90 The N. end of a frame house, bears South, 3 lks. dist.

30.00 Enter open land, edge bears NE. and SW.

33.60 Rice Creek, 15 lks. wide, 6 ins. deep, course N. 10° E.; asc. 30 ft.  
over SE. slope.

38.32 The  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, perpetuated with a steel spring  
leaf, firmly driven in the ground, located in a woven wire fence  
which bears N. and S. The Douglas County records show that this  
spring leaf was set by Arthur Boyer, Deputy County Surveyor, in  
1940, from evidence of the original survey. This point is locally  
accepted as the original corner.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the  
ground, with brass cap mkd.

$\frac{1}{4}$  S 8  
 $\frac{1}{4}$  S 17  
T 29 S R 6 W  
1958

FOOK PER JOHNSTONE  
12-89 M101-72

from which the remains of trees marked by Boyer:

A sawed fir stump, 14 ins. diam., bears N. 81 $\frac{1}{4}$ ° W., 105  
lks. dist., mkd. BT on bark.

A sawed fir stump, 30 ins. diam., bears S. 21 $\frac{1}{2}$ ° W., 106  
lks. dist., no marks remain.

and new bearing trees:

A maple, 10 ins. diam., bears N. 81° E., 190 lks. dist.,  
mkd.  $\frac{1}{4}$  S 8 BT.

A fir, 14 ins. diam., bears N. 45° W., 126 lks. dist.,  
mkd.  $\frac{1}{4}$  S 8 BT.

There is no tree available in sec. 17.

Bury spring leaf alongside the iron post.

N. 89°30' W., beginning new measurement.

Ascend 400 ft. over SE. slope, to spur, through medium timber.

0.35 Rice Creek Road, 40 lks. wide, bears N. and S.

8.10 Corner of woven wire fences extending N., S. and W.; continue  
along fence.

16.70 Spur, slopes N. 60° E.; desc. 15 ft. along N. slope.