

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS
19.43

Point for the W 1/16 sec. cor. of secs. 8 and 17.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S 8}{S 17}$
T 29 S R 6 W
1958

from which

A fir, 20 ins. diam., bears N. 86° W., 38 lks. dist., mkd. W 1/16 S8 BT.

A fir, 9 ins. diam., bears S. 27° E., 11 lks. dist., mkd. W 1/16 S17 BT.

Cor. is located in fence row, extends E. and W.

Descend 210 ft. over NW. slope.

29.60 Draw, drains N.; asc. 80 ft. over NE. slope.

34.20 Spur, slopes N.; desc. 80 ft. over NW. slope.

38.86 The cor. of secs. 7, 8, 17, and 18.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, madrona, maple, oak, hemlock and alder.

Undergrowth, young timber, poison oak, hazel and vines.

N. 89°53' W., bet. secs. 7 and 18.

Descend 100 ft. over NW. slope, through medium timber.

8.90 Porter Creek Road, 20 lks. wide, bears NE. and SW.

9.70 Porter Creek, 4 lks. wide, 4 ins. deep, course N. bending to NE.; asc. 190 ft. over SE. slope.

22.95 Spur, slopes S.; desc. 65 ft. over SW. slope.

36.90 Draw, drains SE.; dirt road, in draw, 10 lks. wide, bears NW. and SE.; asc. 40 ft. over NE. slope.

42.64 Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

1/4 $\frac{S 7}{S 18}$
T 29 S R 6 W
1958

from which

A fir, 14 ins. diam., bears N. 27° W., 161 lks. dist., mkd. 1/4 S7 BT.

A hemlock, 18 ins. diam., bears S. 58° W., 82 lks. dist., mkd. 1/4 S18 BT.

Ascend 110 ft. over NE. slope.

8/2/83 PER
LANDOWNER MRS. C
SONIERMISTER;
TREE CUT FOR LOGGING
STUMP W/TAG LEFT.
J.R.