

County Surveyor's Record, Douglas County, Oregon

12822

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS	
49.15	Head of draw, drains NE.; asc. 320 ft. over SE. slope.
60.33	Ridge, bears NE. and SW.; logging road, bears NE. and SW., along top of ridge; asc. 50 ft. along N. slope.
63.96	Point for the W 1/16 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} W\ 1/16\ \frac{S\ 7}{S\ 18} \\ T\ 29\ S\ R\ 6\ W \\ 1958 \end{array}$
	from which
	A fir, 7 ins. diam., bears N. 79° E., 87 lks. dist., mkd. W 1/16 S7 BT.
	A fir, 10 ins. diam., bears S. 25° W., 75 lks. dist., mkd. W 1/16 S18 BT.
	Ascend 10 ft. over NE. slope.
65.90	Spur, slopes N.; desc. 100 ft. over NW. slope.
72.00	Draw, drains N.; asc. 80 ft. over NE. slope.
77.60	Spur, slopes N. 15° W.; desc. 285 ft. over NW. slope.
87.73	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the 1959 resurvey record.
	Land, mountainous. Soil, rocky clay. Timber, fir, cedar, oak, madrona, hemlock, maple and alder. Undergrowth, young timber, poison oak, hazel, arrowwood, blackberry, vines and ferns.
	From the cor. of secs. 7, 8, 17, and 18.
	N. 1°38' E., bet. secs. 7 and 8.
	Descend 140 ft. over NW. slope, through medium timber.
6.16	Porter Creek Road, 25 lks. wide, bears NE. and SW.
6.50	Driveway, bears E. and W.
7.35	Porter Creek, 3 lks. wide, course NE.; asc. 90 ft. over SE. slope, through scattered timber.
15.60	Spur, slopes E.; desc. 65 ft. over NE. slope.
20.00	Stream, 1 lk. wide, course SE.; asc. 335 ft. over SE. slope, through medium timber.
38.80	Spur, slopes S. 55° E.
38.96	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, perpetuated with an iron pipe, $\frac{3}{4}$ in. diam., 6 ins. above ground, firmly set. The Douglas County records show that this pipe was set by Gene E. Johnson, R. E. 3561,