

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 6 W.

CHAINS

in 1953, from evidence of the original survey and from sworn testimony of Harrison Rice, a local resident, who had knowledge of the cor. position. This point is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 7 | S 8
T 29 S | R 6 W
1958

*FO. OK 7/83
E. Bloom
C.S. 58/292*

from which trees marked by Johnson:

A fir snag, 12 ins. diam., bears S. 69° E., 57 lks. dist., mkd. $\frac{1}{4}$ S RE3561 BT on open blaze.

A fir, 14 ins. diam., bears S. $72\frac{1}{2}^\circ$ W., 38 lks. dist., mkd. $\frac{1}{4}$ S RE3561 BT on open blaze.

and a new bearing tree:

A fir, 8 ins. diam., bears N. 7° E., 101 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

N. $1^\circ 34'$ E., beginning new measurement.

Descend 190 ft. over NE. slope, through medium timber.

10.20 Draw, drains E.; asc. 200 ft. over broken SE. slope.

19.37 Point for the N 1/16 sec. cor. of secs. 7 and 8.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16
S 7 | S 8
T 29 S | R 6 W
1958

from which

A fir, 7 ins. diam., bears S. 51° E., 5 lks. dist., mkd. N 1/16 S8 BT.

A fir, 15 ins. diam., bears S. 52° W., 70 lks. dist., mkd. N 1/16 S7 BT.

Ascend 225 ft. over broken SE. slope.

29.10 Ridge, bears N. 80° E. and S. 80° W.; woven wire fence, bears E. and W.; desc. 200 ft. over NW. slope, changing to W. slope.

38.74 The cor. of secs. 5, 6, 7, and 8, determined from bearing trees marked by G. G. Stewart, Deputy County Surveyor, in 1921. The Douglas County records show that Stewart recovered this cor. in 1921, from two original bearing trees and marked new bearing trees at that time.

At the corner point