

Remonumentation of Certain Corners in T. 29 S., R. 6 W.

CHAINS

(Restoring the survey by Nathaniel Ford, in 1854)

The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., has been perpetuated with an iron post, 1 in. diam., 12 ins. above ground, firmly set, with brass cap mkd. County Surveyors T29S R6W sec 34 35 cor 3 2 T30S R6W 19 Office 56. The Douglas County records show that this cor. was monumented by James W. Byron, Deputy County Surveyor, in 1956, from old bearing trees, not of record. The monument is accepted as the best available evidence of the original corner position.

2/22/78  
SEE LETTER  
ATTACHED TO  
NOTES  
IN C.S. 47/93

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T 29 S R 6 W  
S 34 | S 35  
S 3 | S 2  
T 30 S R 6 W  
1958

from which trees marked by Byron in 1956:

A fir, 6 ins. diam., bears N.  $32\frac{1}{4}^\circ$  E., 84 lks. dist., mkd. T29S R6W S35 CS BT.

A fir, 30 ins. diam., bears S.  $10\frac{3}{4}^\circ$  E., 52 lks. dist., mkd. T30S R6W S2 CS BT.

and new bearing trees:

A cedar, 36 ins. diam., bears S.  $25\frac{3}{4}^\circ$  W., 53 lks. dist., mkd. T30S R6W S3 BT.

A fir, 33 ins. diam., bears N.  $60\frac{1}{2}^\circ$  W., 72 lks. dist., mkd. T29S R6W S34 BT.

Bury the County Surveyor's monument alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 34 and 3, on the S. bdy. of the Tp., is monumented with an iron post, 1 in. diam., 10 ins. above ground, firmly set, with brass cap mkd. County Surveyors T29S R6W  $\frac{1}{4}$  S 34 3 1956 T30S R6W Office. The Douglas County records show that this monument was set by James W. Byron, Deputy County Surveyor, in 1956, who reestablished the cor. at midpoint and on line bet. the section corners.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T 29 S R 6 W  
 $\frac{1}{4}$  S 34  
S 3  
T 30 S R 6 W  
1958

from which bearing trees marked by Byron in 1956:

A fir, 36 ins. diam., bears N.  $37^\circ$  E.,  $34\frac{1}{2}$  lks. dist., mkd. T29S R6W  $\frac{1}{4}$  S34 CS BT.

A fir, 42 ins. diam., bears S.  $59\frac{1}{2}^\circ$  E., 57 lks. dist., mkd. T30S R6W  $\frac{1}{4}$  S3 CS BT.

Bury the County Surveyor's monument alongside the iron post.