

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the S. Bdy., T. 28 S., R. 9 W.

CHAINS	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 28 S</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 9 W</td><td style="padding: 0 5px;">R 8 W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 36</td><td style="padding: 0 5px;">S 31</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> <tr><td colspan="2">T 29 S</td></tr> <tr><td colspan="2">1959</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears S. 43½° E., 56 lks. dist., mkd. T29S R8W S6 BT.</p> <p style="margin-left: 40px;">A maple, 5 ins. diam., bears N. 52½° W., 65 lks. dist., mkd. T28S R9W S36 BT.</p> <p style="margin-left: 40px;">Deposit iron pipe alongside iron post.</p> <p>N. 89° 55' W., between secs. 1 and 36, marking and blazing the true line.</p> <p>Descend 5 ft. over gentle SW. slope, along the S. edge of logged area, through dense undergrowth.</p> <p>1.23 Creek, 5 lks. wide, course S.; asc. 235 ft. over NE. slope, changing to E. slope.</p> <p>36.73 Spur, slopes S.; desc. 55 ft. over W. slope.</p> <p>39.60 Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 28 S</td></tr> <tr><td colspan="2">R 9 W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">¼ S 36</td><td style="padding: 0 5px;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;"></td></tr> <tr><td colspan="2">T 29 S</td></tr> <tr><td colspan="2">1959</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A white fir, 9 ins. diam., bears N. 29¾° W., 34½ lks. dist., mkd. ¼ S36 BT.</p> <p style="margin-left: 40px;">A white fir, 8 ins. diam., bears S. 30° E., 55½ lks. dist., mkd. ¼ S1 BT.</p> <p>The corner falls in the head of a ravine, draining S.; asc. 18 ft. over SE. slope.</p> <p>40.93 Top of ascent, slopes S.; desc. 66 ft. over SW. slope.</p> <p>45.64 Creek, 10 lks. wide, course SE.; asc. 199 ft. over SE. slope.</p> <p>59.65 Top of ascent, slopes S.; desc. 21 ft. over SW. slope.</p> <p>66.70 Ravine, drains S. 30° E.; asc. 338 ft. over E. slope, changing to SE. slope.</p>	T 28 S		R 9 W	R 8 W	S 36	S 31	S 1	S 6	T 29 S		1959		T 28 S		R 9 W		¼ S 36		S 1		T 29 S		1959	
T 28 S																									
R 9 W	R 8 W																								
S 36	S 31																								
S 1	S 6																								
T 29 S																									
1959																									
T 28 S																									
R 9 W																									
¼ S 36																									
S 1																									
T 29 S																									
1959																									