

Dependent Resurvey of Portion of the S. Bdy., T. 28 S., R. 9 W.

CHAINS
79.20

Point for the cor. of secs. 1, 2, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap mkd.

T 28 S
R 9 W
S 35 | S 36
S 2 | S 1
T 29 S
1959

from which

A fir, 10 ins. diam., bears N. 45° E., 18 lks. dist., mkd. T28S R9W S36 BT.

A fir, 10 ins. diam., bears S. $45\frac{1}{2}^\circ$ E., $49\frac{1}{2}$ lks. dist., mkd. T29S R9W S1 BT.

A fir, 11 ins. diam., bears S. $77\frac{3}{4}^\circ$ W., 15 lks. dist., mkd. T29S R9W S2 BT.

A fir, 10 ins. diam., bears N. 23° W., 32 lks. dist., mkd. T28S R9W S35 BT.

Land, mountainous.

Soil, rocky clay loam and clay loam.

Timber, fir, hemlock, cedar, white fir, madrone, chinquapin, dogwood, and yew; undergrowth, salal, Oregon grape, rhododendron, vine maple, manzanita, fern, and arrowwood.

N. $89^\circ 55'$ W., between secs. 2 and 35.

Descend 99 ft. along S. slope, through heavy timber and dense undergrowth.

4.00 Ravine, drains S. 60° E.; asc. 205 ft. over NE. slope.

8.66 Spur, slopes S. 60° E.; asc. 533 ft. over SE. slope, changing to E. slope.

20.07 Spur ridge, bears N. and S. 30° E.; desc. 250 ft. over W. slope.

36.41 Creek, 5 lks. wide, course S.; asc. 51 ft. over SE. slope.

39.60 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 28 S
R 9 W
 $\frac{1}{4}$ S 35
S 2
T 29 S
1959

from which

A hemlock, 8 ins. diam., bears N. $58\frac{1}{4}^\circ$ W., $46\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S35 BT.

A fir, 30 ins. diam., bears S. $78\frac{3}{4}^\circ$ W., $56\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S2 BT.

Ascend 6 ft. along S. slope.