

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the S. Bdy., T. 28 S., R. 9 W.

CHAINS

- 39.92 Spur, slopes S.; desc. 24 ft. over SW. slope.
- 43.84 Creek, 2 lks. wide, course SE.; asc. 293 ft. over SW. slope.
- 48.94 Spur, slopes S.; desc. 318 ft. over SW. slope.
- 61.00 Creek, 2 lks. wide, course S. 10° W.; along broken S. slope.
- 62.23 Creek, 2 lks. wide, course S. 20° E.; asc. 638 ft. over SE. slope.
- 78.90 Dirt access road, 15 lks. wide, bears NE. and SW.
- 79.20 The cor. of secs. 2, 3, 34, and 35, determined at record bearing and distance to the face, from the remains of the original bearing trees:
- A fir, 40 ins. diam., bears N. 38° E., 35½ lks. dist.,
bark scribed T28S R9W S35 BT. (Record distance, 33 lks.)
- A fir snag, 21 ins. diam., bears S. 58° W., 33½ lks. dist.,
bark scribed T29S R9W S3 BT. (Record distance, 32 lks.)
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T 28 S R 9 W
 S 34 S 35
 S 3 S 2
 T 29 S
 1959

from which

- A fir, 13 ins. diam., bears S. 3¼° E., 116 lks. dist.,
mkd. T29S R9W S2 BT.
- A hemlock, 30 ins. diam., bears S. 71° W., 101 lks. dist.,
mkd. T29S R9W S3 BT.
- A hemlock, 10 ins. diam., bears N. 70½° W., 85½ lks. dist.,
mkd. T28S R9W S34 BT.

Land, mountainous.

Soil, rocky clay loam and clay loam.

Timber, fir, hemlock, cedar, white fir, madrone, chinquapin, dogwood, and yew; undergrowth, rhododendron, salal, Oregon grape, vine maple, manzanita, fern, and arrowwood.

Dependent Resurvey of a Portion of the East Boundary,
T. 28 S., R. 9 W., Willamette Meridian, Oregon
(Restoring the 1855 survey by Dennis Hathorn)

From the cor. of Tps. 28 and 29 S., Rs. 8 and 9 W.

N. 0° 23' E., bet. secs. 31 and 36, marking and blazing the true line.

Ascend 117 ft. over gentle S. slope, along E. edge of logged area, through scattered timber and undergrowth.