

Dependent Resurvey of Portion of the E. Bdy., T. 28 S., R. 9 W.

CHAINS

7.35

From this point the SE. cor. of a wood frame dwelling, bears W. 20 lks. dist., dimensions 30 x 24 ft., long side bears E. and W.

20.05

The S 1/16 sec. cor. of secs. 31 and 36, recorded by C. A. Stephens, Registered Surveyor, in 1958, monumented with an iron pipe, 1 in. diam., firmly set, 24 ins. above ground,

from which

A cedar, 12 ins. diam., bears S. 45° E., 5 lks. dist., mkd. BT S 1/16 S31 T28S R8W.

A fir, 10 ins. diam., bears N. 89 $\frac{1}{4}$ ° W., 38 lks. dist., mkd. BT S 1/16 S36 T28S R9W.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S  
S 1/16  
R 9 W | R 8 W  
S 36 | S 31  
1959

N. 0° 13' E., beginning new measurement.

Ascend 109 ft. over SE. slope.

7.02

Dirt access road, 15 lks. wide, bears E. and W.

10.10

Top of ascent, slopes SE.; desc. 86 ft. over NE. slope.

20.08

The  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1957, monumented with an axle, 1 in. diam., firmly set, 8 ins. above ground, from which the original bearing trees:

A rotted fir stump, 40 ins. diam., bears S. 85° E., 11 lks. dist. (Record bearing, S. 80° E.)

A down fir, 50 ins. diam., bears N. 20° W., 18 lks. dist., with scribe marks BT visible on an opened blaze.

and locally established bearing tree

A cedar, 27 ins. diam., bears S. 43 $\frac{1}{4}$ ° E., 66 lks. dist., with scribe marks  $\frac{1}{4}$  S CS BT visible on open blaze.

and bearing tree established by Byron

A white fir, 5 ins. diam., bears S. 59 $\frac{1}{2}$ ° W., 36 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S36 DCS BT.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.

T 28 S  
 $\frac{1}{4}$   
R 9 W | R 8 W  
S 36 | S 31  
1959