

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the Subdivisional Lines, T. 28 S., R. 9 W.

CHAINS

T 28 S R 9 W

 $\frac{1}{4}$ S 25

S 36

1959

from which

A fir, 7 ins. diam., bears N. $72\frac{3}{4}^{\circ}$ E., 35 lks. dist.,
mkd. $\frac{1}{4}$ S25 BT.

A fir, 6 ins. diam., bears S. $20\frac{1}{4}^{\circ}$ E., $12\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S36 BT.

Ascend 43 ft. over E. slope.

- 42.53 Spur, slopes S. 30° E.; desc. 135 ft. over SW. slope.
49.91 Creek, 7 lks. wide, course S. 30° E.; asc. 211 ft. over E. slope.
54.23 Spur, slopes S. 30° E.; asc. 33 ft. along broken S. slope.
62.08 Creek, 4 lks. wide, course SE.; asc. 250 ft. over E. slope.
66.91 Spur, slopes SE.; asc. 339 ft. along S. slope.
80.43 The cor. of secs. 25, 26, 35, and 36.

Land, mountainous.

Soil, clay loam and rocky clay loam.

Timber, fir, hemlock, cedar, white fir, madrone, chinquapin, maple,
dogwood, and alder; undergrowth, salal, Oregon grape, rhododendron,
vine maple, manzanita, fern, arrowwood, hazel, huckleberry, and
elderberry.

N. $1^{\circ} 09'$ E., bet. secs. 25 and 26.

Ascend 208 ft. over S. slope, through heavy timber and dense undergrowth.

- 5.48 Dirt access road, 15 lks. wide, bears N. 60° E. and S. 60° W.
8.73 Ridge, dividing Middle Fork Coquille River drainage and Camas Creek drainage, bears NE. and SW.; desc. 102 ft. over NW. slope.
17.24 Foot of descent, slopes W.; asc. 10 ft. along W. slope.
21.84 Top of ascent, slopes W.; desc. 16 ft. along W. slope.
24.30 Foot of descent, slopes W.; asc. 49 ft. along W. slope.
30.86 Top of ascent, slopes W.; desc. 10 ft. along W. slope.
32.36 Ravine, drains W.; asc. 34 ft. along W. slope.
34.54 Dirt access road, 30 lks. wide, bears NW. and SE.
37.32 Dirt access road, 15 lks. wide, bears N. 20° E. and S. 20° W.
39.33 The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, determined at record distance from the original bearing trees:

A hemlock, 19 ins. diam., bears N. 88° E., 83 lks. dist. with scribe mark 5 visible on opened blaze.

A hemlock, 15 ins. diam., bears S. $61\frac{1}{4}^{\circ}$ W., 29 lks. dist., with scribe mark T visible on opened blaze. (Record bearing, S. 54° W.)