

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of 6th Stan. Par. S., Portion of N. Bdy. of T. 28 S., R. 8 W.

CHAINS

7.10

Rim, bears NE. and SW., slope changes; desc. 100 ft. over W. slope, along top of spur ridge, through dense timber and undergrowth.

20.20

The E 1/16 sec. cor. of sec. 4, established by G. Robert Lecklider monumented with a chromed iron pipe, $\frac{1}{2}$ in. diam., protruding 18 ins. above ground, set in a small mound of stone, with cap mkd. Property Corner, from which bearing trees mkd. by Lecklider:

A fir, 22 ins. diam., bears S. 32° E., 67 lks. dist., mkd. E 1/16 S4 T28S R8W RPE 4079 BT.

A fir, 30 ins. diam., bears S. 66° W., 26 lks. dist., mkd. E 1/16 S4 T28S R8W RPE 4079 BT and Lecklider's cruiser mark.

Descend 160 ft. over W. slope, along top of spur ridge.

40.00

Point for the $\frac{1}{4}$ sec. cor. of sec. 33, only, on the S. bdy. of T. $27\frac{1}{2}$ S., R. 8 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T $27\frac{1}{2}$ S R 8 W
 $\frac{1}{4}$ S 33
 1961

FD OK PER HINTZ
 DEC 1986 M103-8

from which

A fir, 28 ins. diam., bears N. $53\frac{1}{2}^{\circ}$ E., 24 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

An oak, 9 ins. diam., bears N. 27° W., 18 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

Descend 2 ft. over W. slope.

FD OK PER HINTZ
 DEC 1986 M103-8

40.41

The standard $\frac{1}{4}$ sec. cor. of sec. 4, determined at record bearing and distance from the original SE. bearing tree:

A fir, 25 ins. diam., bears S. 25° E., 20 lks. dist., mkd. with an opened blaze, illegible bark scribing and Lecklider's cruiser mark. Reblaze and mark $\frac{1}{4}$ S4 SC BT.

A piece of fir pitch face, 3 ins. wide, 18 ins. long, mkd. BT, was found lying beside the corner point. Lecklider asserts that this is the remainder of the original NE. bearing tree.

and a tree mkd. by Arthur Boyer, RPE 1581:

A hemlock, 10 ins. diam., bears N. 67° W., 20 lks. dist., mkd. $\frac{1}{4}$ S4 and other illegible scribe marks on a partially overgrown face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.