

Dependent Resurvey of 6th Stan. Par. S., Portion of N. Bdy. of T. 28 S., R. 8 W.

CHAINS  
41.51

The standard  $\frac{1}{4}$  sec. cor. of sec. 5, determined at record bearing and distance from the original SE. bearing tree:

A hemlock, 18 ins. diam., bears S. 10° E., 31 lks. dist., mkd. BT on opened face.

The original NE. bearing tree, a cedar, 30 ins. diam., mkd. with open face, is dead and lying downhill to the NE., with original position lost.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$  S 5  
 T 28 S R 8 W  
 S C  
 1961

from which new bearing trees:

A hemlock, 24 ins. diam., bears S. 65° E., 57 lks. dist., mkd.  $\frac{1}{4}$  S5 SC BT.

A cedar, 50 ins. diam., bears S. 83° W., 19 lks. dist., mkd.  $\frac{1}{4}$  S5 SC BT.

A Bureau of Land Management approximate corner point, number 404, mkd. with 2 in. iron pipe, protruding 18 ins. above ground, bears S. 35° W., 2 lks. dist.

West, beginning new measurement.

Ascend 40 ft. over NE. slope.

- 1.70 Spur, slopes N.; asc. 3 ft. along broken N. slope.
- 6.00 Small ravine, drains N. 20° E.; asc. 240 ft. over general E. slope.
- 13.70 Burnt Ridge, bears N. 30° W. and S. 30° E.; desc. 365 ft. over broken SW. slope.
- 20.00 Burnt Ridge Road, 30 lks. wide, graded and maintained, bears NW. and SE.
- 38.40 Shallow draw, drains N. 65° W.; asc. 5 ft. over NE. slope.
- 40.00 The standard cor. of secs. 5 and 6, remonumented by the Douglas County Surveyor with an iron post, 1 in. diam., protruding 12 ins. above ground, with brass cap mkd. County Surveyor's Office T27S R8W S 32 5 6 T28S R8W 1957, from which the original bearing trees:

A fir, 36 ins. diam., bears S. 50° E., 26 lks. dist., bark scribed T28S R8, and other illegible scribe marks. (Record, 46 lks. dist.)

A fir, 62 ins. diam., bears S. 46° W., 55 lks. dist., bark scribed T28S R8W S6. (Record bears S. 48° W., 53 lks. dist.)

and trees marked by the County Surveyor:

A hemlock, 8 ins. diam., bears S. 84° E., 30 lks. dist., mkd. S5 CS BT.