

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of 6th Stan. Par. S., Portion of N. Bdy. of T. 28 S., R. 8 W.

CHAINS

A yew, 10 ins. diam., bears S. 30° W., 22 lks. dist.,
mkd. T28S R8W S6 CS BT.

A yew, 6 ins. diam., bears N. 71° W., 49 lks. dist.,
mkd. T27S R8W S32 CS BT.

and a tree mkd. by Arthur Boyer, RPE 1581:

A yew, 6 ins. diam., squared at breast height, bears
N. 68° W., 15 lks. dist., mkd. S5 on E. face and S6
on W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd.

S 6	S 5
T 28 S	R 8 W
S C	
1961	

from which a new bearing tree:

A fir, 58 ins. diam., bears S. 29° E., 28 lks. dist.,
mkd. T28S R8W S5 SC BT.

Add the marks SC BT in the bark on original SW. tree.

Deposit County Surveyor's iron post alongside the
corner post.

Land, mountainous.

Soil, rocky clay and clay loam.

Timber, fir, hemlock, cedar, madrone, yew, and oak; undergrowth,
young timber, salal, huckleberry, rhododendron, ceanothus, arrow-
wood, manzanita, vines, ferns, and Oregon grape.

N. 84° 01' W., on the N. bdy. of sec. 6.

Descend 100 ft. over W. slope, through heavy timber and moderate
undergrowth.

5.62

The standard cor. of secs. 31 and 32, on the S. bdy. of T. 27 S.,
R. 8 W., monumented by the Douglas County Surveyor with an iron
post, 1 in. diam., protruding 12 ins. above ground, with brass cap
mkd. County Surveyor's Office T27S R8W SEC 31 32 6 T28S R8W 1957,
from which the original bearing trees, marked by Heydon in 1896:

A fir, 42 ins. diam., bears N. 5° W., 40 lks. dist.,
mkd. in the bark, T R8W, and other illegible scribe
marks. Add the marks SC BT in the bark.

A fir stump, rotted, 30 ins. diam., bears N. 74° E.,
54 lks. dist., no marks remain. (Record, N. 54° E.,
50 lks. dist.)

and trees marked by the County Surveyor:

A yew, 6 ins. diam., bears N. 46° E., 14 lks. dist.,
mkd. T27S R8W S32 CS BT.

A hemlock, 25 ins. diam., bears S. 5° W., 68 lks. dist.,
mkd. T28S R8W S6 CS BT and with local cruiser marks.