

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of 6th Stan. Par. S., Portion of S. Bdy. of T. 28 S., R. 8 W.

CHAINS	
	<p>A hemlock, 12 ins. diam., bears N. 41° E., 6 lks. dist., mkd. T27S R8W S35 SC BT.</p> <p>A cedar, 6 ins. diam., bears N. 31½° W., 41 lks. dist., mkd. T27S R8W S34 SC BT.</p>
	<p>N. 89° 12' W., on the S. bdy. of sec. 34.</p> <p>Descend 3 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
0.15	Draw, drains S. 20° E.; asc. 66 ft. over general SE. slope.
5.10	Spur, slopes S.; desc. 35 ft. over SW. slope.
7.10	Creek, 2 lks. wide, course S. 20° E.; asc. 188 ft. over SE. slope.
14.70	Spur, slopes S.; desc. 40 ft. over SW. slope.
19.00	Ravine, drains S. 45° E.; asc. 40 ft. over SE. slope.
22.10	Wet ravine, drains S. 70° E.; asc. 495 ft. over general E. slope.
29.60	Road, 15 lks. wide, graded and maintained, bears N. 10° E. and S. 10° W.
31.80	Slope changes; asc. 10 ft. over SE. slope.
33.24	Point for the ¼ sec. cor. of sec. 34, only, on the N. bdy. of T. 27½ S., R. 8 W., hereinafter described.
	Ascend 77 ft. over SE. slope.
39.05	<p>The standard ¼ sec. cor. of sec. 34, determined from the original bearing trees:</p> <p>A fir, 35 ins. diam., bears N. 19° W., 32 lks. dist., mkd. with illegible scribe marks at breast height on a previously opened face and BT on opened blaze above the root crown, of proper age, facing the corner.</p> <p>A fir, 40 ins. diam., bears N. 63½° E., 37 lks. dist., mkd. with a very old cruiser mark in the bark, at breast height, but no legible scribe marks. Add marks ¼ S34 SC BT in the wood.</p> <p>The Heydon record calls for a fir, 10 ins. diam., N. 70° E., 32 lks. dist., and a fir, 20 ins. diam., S. 1° W., 37 lks. dist. These bearings cannot be reconciled with the conditions on the ground and the above described position was arrived at as the most logical position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T 27 S R 8 W ¼ S 34 1961</p>
	<p>N. 88° 58' W., beginning new measurement.</p> <p>Ascend 10 ft. over SE. slope.</p>
0.50	Spur ridge, bears N. 65° E. and S. 65° W.; asc. 170 ft. over broken general NE. slope.