

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of 6th Stan. Par. S., Portion of S. Bdy. of T. 28 S., R. 8 W.

CHAINS

- 29.00 Rim, slopes steeply S. 20° E.; desc. 45 ft. along broken S. slope.
- 34.23 Point for the closing corner of secs. 33 and 34, T. 27½ S., R. 8 W., hereinafter described.
- Descend 32 ft. along broken S. slope.
- 39.30 Rim, bears SW. and N. 80° E., in curve; slope changes; desc. 3 ft. over W. slope.
- 40.03 The standard cor. of secs. 33 and 34, perpetuated by G. Robert Lecklider, RPE 4079, with a chromed iron pipe, ½ in. diam., protruding 18 ins. above ground, in a mound of stone, 2 ft. base, to top, with cap mkd. Property Corner. A small portion of the original corner tree, mkd. with illegible scribe marks, was found lying beside the pipe; from which the original bearing trees:
- A fir, 22 ins. diam., bears N. 36° E., 57 lks. dist., mkd. with a healed blaze, and BT on an opened face. (Record bearing, N. 34° E.)
- A fir, 20 ins. diam., bears N. 61° W., 40 lks. dist., mkd. with a burned face.
- and bearing trees mkd. by Lecklider:
- A fir, 22 ins. diam., bears N. 2½° E., 43 lks. dist., mkd. T27S R8W S34 CC BT RE 4079, and Lecklider's cruiser mark.
- A fir, 25 ins. diam., bears N. 71° W., 37 lks. dist., mkd. T27S R8W CC S33 BT RE 4079, and Lecklider's cruiser mark.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
- | | | | |
|------|------|------|---|
| | S | C | |
| T 27 | S | R 8 | W |
| | S 33 | S 34 | |
| | 1961 | | |
- from which a new bearing tree:
- A hemlock, 10 ins. diam., bears N. 29½° W., 16 lks. dist., mkd. T27S R8W S33 SC BT.
- Deposit Lecklider's iron pipe beside iron post.
- Land, mountainous.
Soil, rocky clay and clay loam.
Timber, fir, hemlock, cedar, madrone, oak and yew; undergrowth, salal, huckleberry, ceanothus, arrowwood, rhododendron, young timber, manzanita, vines, ferns, and grass.
-
- N. 89° 19' W., on the S. bdy. of sec. 33.
- Descend 310 ft. over NW. slope, changing to N. slope, through heavy timber and undergrowth.
- 34.21 Point for the ¼ sec. cor. of sec. 33 only, on the N. bdy. of T. 27½ S., R. 8 W., hereinafter described.
- Ascend 30 ft. over NE. slope.
- 38.50 Top of slope, slopes N.; desc. 10 ft. over W. slope.