

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of 6th Stan. Par. S., Portion of S. Bdy. of T. 27 S., R. 8 W.

CHAINS

40.26

The standard $\frac{1}{4}$ sec. cor. of sec. 33, determined at record distance from each of the original bearing trees:

A fir, 38 ins. diam., bears N. 54° E., 37 lks. dist., mkd. with a bark scribed S, (original) and a local cruiser mark. (Record bearing, N. 63° E.). Add the marks $\frac{1}{4}$ S33 SC BT on new blaze.

A rotted fir stump, 18 ins. diam., bears N. 17° W., 43 lks. dist., mkd. $\frac{1}{4}$ S on the remains of a rotted face.

and a bearing tree mkd. by Weyerhaeuser Timber Company:

A fir, 35 ins. diam., bears N. 33° W., 57 lks. dist., mkd. with a spike driven into a small blaze at the root crown.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

S C
T 27 S R 8 W
$\frac{1}{4}$ S 33

1961

from which a new bearing tree:

A hemlock, 10 ins. diam., bears N. $50\frac{1}{2}^{\circ}$ W., 60 lks. dist., mkd. $\frac{1}{4}$ S33 SC BT.

N. $89^{\circ} 01'$ W., beginning new measurement.

Descend 375 ft. over steep SW. slope.

12.50 Foot of steep slope, bears N. 10° W. and S. 10° E.; desc. 270 ft. over moderate SW. slope.

33.96 Point for the closing cor. of secs. 32 and 33, T. $27\frac{1}{2}$ S., R. 8 W., hereinafter described.

Descend 42 ft. over SW. slope.

35.40 Wilson Creek, 10 lks. wide, course N. 30° E.; asc. 290 ft. over steep NE. slope.

38.00 Spur, slopes N. 10° W.; desc. 20 ft. over W. slope.

39.90 Creek, 2 lks. wide, course N. 20° E.; asc. 35 ft. over E. slope.

42.19 The standard cor. of secs. 32 and 33, determined at record bearing and distance from the remaining original bearing tree:

A dead hemlock, 10 ins. diam., bears N. 88° E., 40 lks. dist., mkd. S33 T27S R8W on open face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
T 27 S R 8 W
S 32 S 33

1961