

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of 6th Stan. Par. S., Portion of S. Bdy. of T. 27 S., R. 8 W.

CHAINS

from which new bearing trees:

A hemlock, 43 ins. diam., bears N.  $31\frac{1}{2}^{\circ}$  E., 120 lks. dist., mkd. T27S R8W S33 SC BT.

A hemlock, 26 ins. diam., bears N.  $11^{\circ}$  W., 32 lks. dist., mkd. T27S R8W S32 SC BT.

From this point a Bureau of Land Management approximate corner point, number 405, a 2 in. iron pipe, protruding 18 ins. above ground, bears South, 3 lks. dist.

Land, mountainous.

Soil, rocky clay and clay loam.

Timber, fir, hemlock, cedar, madrone, oak, and yew; undergrowth, young timber, salal, ceanothus, huckleberry, arrowwood, rhododendron, Oregon grape, vines, and ferns.

S.  $87^{\circ} 26'$  W., on the S. bdy. of sec. 32.

Ascend 175 ft. over NE. slope, through heavy timber and dense undergrowth.

6.00 Spur, slopes N.  $10^{\circ}$  W.; desc. 210 ft. over N. slope, changing to NW. slope.

26.40 Ravine, drains NW.; asc. 100 ft. over NE. slope.

31.79 Point for the  $\frac{1}{4}$  sec. cor. of sec. 32, only, on the N. bdy. of T.  $27\frac{1}{2}$  S., R. 8 W., hereinafter described.

Ascend 120 ft. over NE. slope.

34.30 Spur, slopes N.; desc. 10 ft. along N. slope.

38.20 Small ravine, drains N.  $20^{\circ}$  E.; asc. 20 ft. over E. slope.

39.16 The standard  $\frac{1}{4}$  sec. cor. of sec. 32, determined at record distance from each of the original bearing trees:

A cedar, 14 ins. diam., dead and down, bears N.  $43^{\circ}$  E., 36 lks. dist., mkd. SC  $\frac{1}{4}$  S on open blaze. (Record bearing, N.  $40^{\circ}$  E.)

A cedar, 51 ins. diam., bears N.  $3^{\circ}$  W., 33 lks. dist., mkd. with a healed blaze and local cruiser marks. (Record bearing, N.  $8^{\circ}$  W.) Reblaze tree on the overgrowth and mark  $\frac{1}{4}$  S32 SC BT.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

S C  
T 27 S R 8 W  
 $\frac{1}{4}$  S 32  
-----  
1961

from which

A hemlock, 15 ins. diam., bears N.  $68^{\circ}$  E., 112 lks. dist., mkd.  $\frac{1}{4}$  S32 SC BT with a Weyerhaeuser Timber Company spike, driven in a small blaze at the root crown.