

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of 6th Stan. Par. S., Portion of S. Bdy. of T. 27 S., R. 8 W.

CHAINS

From this point a Bureau of Land Management approximate corner point number 403, 2 in. iron pipe, protruding 30 ins. above ground, bears S. 74° E., 2 lks. dist.

S. 88° 26' W., beginning new measurement.

Ascend 255 ft. over general E. slope.

8.00 Burnt Ridge, bears N. 35° W. and S. 35° E.; desc. 470 ft. over broken SW. slope.

14.70 Burnt Ridge Road, 30 lks. wide, graded and maintained, bears NW. and SE.

39.08 The standard cor. of secs. 31 and 32, T. 27 S., R. 8 W., and cor. of sec. 32, T. 27½ S., R. 8 W., hereinbefore described.

Land, mountainous.

Soil, rocky clay and clay loam.

Timber, fir, hemlock, cedar, madrone, and yew; undergrowth, young timber, salal, huckleberry, ceanothus, arrowwood, manzanita, Oregon grape, rhododendron, vines and ferns.

Survey of the Subdivisional Lines of T. 27½ S., R. 8 W.

From the standard cor. of secs. 3 and 4, T. 28 S., R. 8 W., and cor. of secs. 33 and 34, T. 27½ S., R. 8 W.

N. 0° 01' W., bet. secs. 33 and 34.

Ascend 50 ft. over steep S. slope, through scattered timber and light undergrowth.

1.30 Intersect the 6th Standard Parallel South, S. bdy. of T. 27 S., R. 8 W.

Point for the closing cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 27 S R 8 W	
S 34	
S 33	S 34
T 27½ S	R 8 W
C C	
1961	

from which

A fir, 7 ins. diam., bears S. 72½° E., 33 lks. dist., mkd. T27½S R8W S34 CC BT.

A fir, 6 ins. diam., bears S. 45° W., 17 lks. dist., mkd. T27½S R8W S33 CC BT.

From this point the standard cor. of secs. 33 and 34, T. 27 S., R. 8 W., bears N. 88° 58' W., 5.80 chs. dist.

To complete the survey of sec. 34, at midpoint in departure on the N. bdy. of sec. 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.