

Survey of the Subdivisional Lines, of T. 27 $\frac{1}{2}$ S., R. 8 W.

CHAINS

$\frac{1}{4}$ S 34
 T 27 $\frac{1}{2}$ S R 8 W
 1961

from which

A fir, 26 ins. diam., bears S. 61 $\frac{1}{2}$ ° E., 71 lks. dist.,
mkd. $\frac{1}{4}$ S34 BT.

A fir, 28 ins. diam., bears S. 75° W., 79 lks. dist.,
mkd. X only at breast height.

From this point the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 27 S.,
R. 8 W., bears N. 89° 12' W., 5.81 chs. dist.

From the same point, the standard $\frac{1}{4}$ sec. cor. of sec. 3, T. 28 S.,
R. 8 W., and $\frac{1}{4}$ sec. cor. on S. bdy. of sec. 34, T. 27 $\frac{1}{2}$ S., R. 8 W.,
bears South, 0.67 chs. dist.

From the cor. of secs. 32 and 33, on S. bdy. of the Tp.

N. 0° 02' W., bet. secs. 32 and 33.

Descend 110 ft. over NE. slope, through heavy timber and dense
undergrowth.

3.25 Wilson Creek, 10 lks. wide, course NW.; asc. 40 ft. over SW. slope.

4.635 Intersect the 6th Standard Parallel South, S. bdy. of T. 27 S.,
R. 8 W.

Point for the closing corner of secs. 32 and 33.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the
ground, with brass cap mkd.

T 27 S R 8 W
 S 33
 S 32 | S 33
 T 27 $\frac{1}{2}$ S | R 8 W
 C C
 1961

from which

A hemlock, 16 ins. diam., bears S. 34° E., 58 lks. dist.,
mkd. T27 $\frac{1}{2}$ S R8W S33 CC BT.

A cedar, 16 ins. diam., bears S. 43 $\frac{1}{2}$ ° W., 129 lks. dist.,
mkd. T27 $\frac{1}{2}$ S R8W S32 CC BT.

From this point the standard cor. of sec. 32 and 33, T. 27 S.,
R. 8 W., bears N. 89° 01' W., 8.23 chs. dist.

To complete the survey of sec. 33, at midpoint in departure on the
N. bdy. of sec. 33.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the
ground, to solid rock, and in a mound of stone, 2 ft. base, to top,
with brass cap mkd.

$\frac{1}{4}$ S 33
 T 27 $\frac{1}{2}$ S R 8 W
 1961

from which