

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS

From the cor. of secs. 28, 29, 32 and 33, determined from the remaining original bearing trees:

A madrone, 18 ins. diam., bears S. 61° E., 50 lks. dist., (slope dist., 55 lks.) with fragmentary scribe marks visible on bark. (Record bearing and distance, S. 62° E., 55 lks.)

A madrone, 24 ins. diam., bears S. 52° W., 78 lks. dist., (slope dist., 82 lks.) with no marks remaining. (Record bearing and distance, S. 58° W., 82 lks. dist.)

A fir turn out, 50 lks. diam., the stump hole of which bears N. 64° W., 60 lks. dist., (slope dist., 66 lks.) with no marks remaining. (Record bearing and distance, N. 42° W., 66 lks.)

There is no remaining evidence of the NE. bearing tree.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T22S R8W	
S 29	S 28
S 32	S 33
1960	

from which new bearing trees

A douglas fir, 9 ins. diam., bears S. 35° W., 102 lks. dist., mkd. T22S R8W S32 BT.

A white fir, 6 ins. diam., bears N. 38° W., 45 lks. dist., mkd. T22S R8W S29 BT.

no suitable bearing tree available to the NE.

From this point the SW. cor. of Donation Land Claim No. 44, bears N. 4° 07' W., 22,29 chs. dist., monumented with the original fir snag, 40 ins. diam., with fragmentary scribe marks visible on bark, on N. face, from which

A sawed fir stump, 40 ins. diam., bears N. 25° E., 19 lks. dist., with no marks remaining.

A sawed fir stump, 39 ins. diam., bears S. 88° W., 14 lks. dist., with no marks remaining.

No permanent monument established.

S. 89° 49' W., bet. secs. 29 and 32.

Descend 490 ft. over SW. slope, changing to W. slope, through logged area and heavy brush.

19.76

Point for the E. 1/16 sec. cor. of secs. 29 and 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16	S 29
	S 32
1960	

from which