

County Surveyor's Record, Douglas County, Oregon

6

Dependent Resurvey of Portion of Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS	slope.
19.77	Point for the E. 1/16 sec. cor. of secs. 30 and 31. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{E } 1/16 \text{ } \frac{\text{S } 30}{\text{S } 31} \\ 1960 \end{array}$ from which A fir, 28 ins. diam., bears N. 1° E., 135 lks. dist., mkd. E 1/16 S30 BT. A fir, 8 ins. diam., bears S. 38° W., 36 lks. dist., mkd. E 1/16 S31 BT. Descend 376 ft. over broken NW. slope.
39.54	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \frac{\text{S } 30}{\text{S } 31} \\ \text{T22S, R8W} \\ 1960 \end{array}$ from which A fir, 15 ins. diam., bears N. 86° E., 96 lks. dist., mkd. 1/4 S30 BT. A fir, 8 ins. diam., bears S. 8° E., 121 lks. dist., mkd. 1/4 S31 BT. Descend 270 ft. over broken NW. slope.
47.50	Creek, 10 lks. wide, course N. 10° W.; asc. 29 ft. over NE. slope.
51.15	Spur, slopes N. 30° E.; desc. 12 ft. over NW. slope.
53.00	Branch, 3 lks. wide, course NE.; asc. 548 ft. over SE. slope.
73.40	Ridge, bears N. and S.; desc. 237 ft. over SW. slope, changing to S. slope.
85.16	The cor. of secs. 30 and 31, only, on the W. bdy. of the township, determined at record distance from the remaining original bearing trees as described by E. O. Warrick in 1894: A fir, 44 ins. diam., bears N. 8° E., 92 lks. dist., with a healed blaze. A rotted fir stump, size indeterminate, bears S. 77° E., 131 lks. dist., with no marks remaining. (record bearing, S. 74° E.) A rotted fir stump, size indeterminate, bears S. 88° W., 137 lks. dist., with no marks remaining. (Record bearing, S. 84° W.) A rotted fir stump, size indeterminate, bears N. 70° W., 66 lks. dist., with no marks remaining. (Record bearing, N. 67° W.) At the corner point