

## County Surveyor's Record, Douglas County, Oregon

T. 20 S., R. 8 W.

## CHAINS

The following is the remonumentation of certain original corner points, township 20 south, range 8 west, of the Willamette Meridian, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories When Needed."

The remonumentation of these corners was requested by the Coos Bay District Manager, for administrative purposes of the Bureau of Land Management,

(Remonumentation of the  $\frac{1}{4}$  section corner of Sections 12 and 13, Established by W. P. Wright in 1884; Reestablished by R. M. Bicknell in 1954.)

The  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

$\frac{1}{4}$  S 12  
S 13  
1954

from which

The stump hole of a turned out fir, bears N. 9° E., 52 lks. dist. The fir, 24 ins. diam., lies several chains downhill.

The stump hole of a turned out fir, bears S. 41° E., 33 lks. dist. The fir, 39 ins. diam., lies several chains downhill.

add new bearing trees:

A cedar, 7 ins. diam., bears N. 47° E., 34 lks. dist., mkd.  $\frac{1}{4}$  S12 BT.

A cedar, 10 ins. diam., bears S. 44° E., 88 lks. dist., mkd.  $\frac{1}{4}$  S13 BT.

(Remonumentation of the  $\frac{1}{4}$  section corner of Sections 28 and 33, Established by W. P. Wright in 1884; Reestablished by T. A. Tillman in 1950.)

The  $\frac{1}{4}$  sec. cor. of secs. 28 and 33 was removed by the Bureau of Public Roads in 1958 while in the process of building an access road along the Smith River. At the time of their work they established reference points for the  $\frac{1}{4}$  sec. cor. These reference points were hubs set in line at points 300 feet and 500 feet north-easterly and 300 feet and 600 feet southeasterly from the corner. These points were subsequently recovered and the  $\frac{1}{4}$  sec. cor. re-established from them.

At the corner point, which falls in the east edge of a curve of a gravelled access road, 30 lks. wide, bearing NW. and SE.

Set a steel shaft collar, 4 ins. diam.,  $1\frac{1}{2}$  in. thick, with a  $1\frac{1}{4}$  in. bore, 8 ins. below the road surface.

from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° E., 130 lks. dist., with brass cap mkd.  $\frac{1}{4}$  S28 RM 1960 and an arrow pointing to the corner.