

## County Surveyor's Record, Douglas County, Oregon

## CHAINS

The following is the remonumentation of certain original corner points, township 21 south, range 8 west, of the Willamette Meridian, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories When Needed."

The remonumentation was requested by the Coos Bay District Manager for administrative purposes of the Bureau of Land Management.

(Remonumenting the corners established by William P. Wright in 1883 and reestablished by Normen D. Price and George F. Rigby in 1945)

The cor. of secs. 7 and 18, only, on the W. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees and from the remains of the bearing trees marked in 1945:

A turned out fir, 22 ins. diam., bears N.  $18\frac{1}{2}^{\circ}$  E., 45 lks., with no marks remaining on burned and rotted blaze. (1945)

The decayed remains of a hemlock stump, bears N.  $69\frac{1}{2}^{\circ}$  E., 47 lks. dist., with no marks remaining. (Original)

A turned out fir, 32 ins. diam., bears S.  $57\frac{1}{4}^{\circ}$  E., 155 lks. dist., with scribe marks T21S R8W visible on unhealed blaze. (1945)

The decayed remains of a hemlock stump, bears S.  $43^{\circ}$  E., 44 lks. dist., with no marks remaining. (Original)

The decayed remains of a hemlock stump, bears S.  $58^{\circ}$  W., 52 lks. dist., with no marks remaining. (Original)

At the corner point

Reset the iron post, 36 ins. long, 2 ins. diam., which had been pulled up and was lying on the ground, 30 ins. in the ground, with brass cap marked

T21S	T21S
R9W	S 7
S 12	S 18
	R8W
	1945

from which new bearing trees:

A fir, 3 ins. diam., bears S.  $87^{\circ}$  E., 74 lks. dist., mkd. BT only.

A fir, 3 ins. diam., bears S.  $43\frac{1}{2}^{\circ}$  E., 38 lks. dist., mkd. BT only.

No other suitable bearing tree available.

The  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, determined at record bearing and distance from the SW. bearing tree:

A sawed fir stump, 48 ins. diam., bears S.  $53\frac{1}{2}^{\circ}$  W., 166 lks. dist., with scribe marks  $\frac{1}{4}$  visible on burned surface of unhealed blaze.

At the corner point