

County Surveyor's Record, Douglas County, Oregon

T. 23 S., R. 9 W.

CHAINS

The following is the remonumentation of the one-quarter section corner of sections 15 and 16, township 23 south, range 9 west, of the Willamette Meridian, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, With New Accessories When Needed."

The remonumentation of the corner was made at the request of the Coos Bay District Manager, for administrative purposes of the Bureau of Land Management.

(Remonumentation of the Corner Established by Oscar F. Thiel in 1898.)

The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, determined at record bearing and distance from the remaining original bearing tree:

A hemlock snag, 30 ins. diam., bears N. 10° W., 54 lks. dist., with scribe marks $\frac{1}{4}$ S16 BT visible on unhealed blaze.

At the corner point,

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 16 | S 15
 T 23 S R 9 W.
 1960

from which new bearing trees:

*FD. OK 2/10/75 G. LANGLITZ, Surveyor's
OFFICE. C.S. 57/17*

A hemlock, 13 ins. diam., bears S. 4° E., 126 lks. dist., mkd. $\frac{1}{4}$ S15 BT.

A fir, 6 ins. diam., bears S. 67 $\frac{1}{2}$ ° W., 79 lks. dist., mkd. $\frac{1}{4}$ S16 BT.