

County Surveyor's Record, Douglas County, Oregon

-2-

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 11 W.

CHAINS

T 21 S R 11 W	
S 22	S23
S 27	S26
1960	

from which:

A fir, 8 ins. diam., bears N. $21\frac{1}{2}^{\circ}$ E., 13 lks. dist.,
mkd. T21S R11W S23 BT.

A fir, 15 ins. diam., bears S. 35° E., 7 lks. dist.,
mkd. T21S R11W S26 BT.

A fir, 13 ins. diam., bears S. 87° W., 12 lks. dist.,
mkd. T21S R11W S27 BT.

A fir, 10 ins. diam., bears N. 13° W., 26 lks. dist.,
mkd. T21S R11W S22 BT.

Deposit the original corner stone alongside the iron post.

From this point, a witness point between secs. 26 and 27, bears
S. $0^{\circ} 01'$ E., 9.21 chs. dist., determined at record bearing and
distance from the only remaining original bearing tree:

A sawed fir stump, 52 ins. diam., 14 ft. high, bears
N. 29° E., 47 lks. dist., with scribe marks S26 BT
visible on bark.

At the point for the witness point, which falls in a dirt access
road, 15 lks. wide, bearing E. and W.

Set an iron pipe, 16 ins. long, 1 in. diam., 28 ins. in the road,
for a perpetuation of the witness point.

N. $0^{\circ} 47'$ W., bet. secs. 22 and 23, marking and blazing the true line.

Ascend 109 ft. over S. slope, through heavy timber and dense
undergrowth.

2.40 Spur, slopes N. 75° W.; desc. 124 ft. over N. slope.

5.50 Ravine, course NW.; asc. 17 ft. over SW. slope.

7.00 Spur, slopes N. 35° W.; desc. 89 ft. over N. slope.

8.60 Ravine, course N. 65° W.; asc. 166 ft. over SW. slope.

13.80 Spur, slopes N. 80° W.; desc. 84 ft. over broken NW. slope.

20.15 Point for the S $1/16$ sec. cor. of secs. 22 and 23.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the
ground with brass cap mkd.

S $1/16$	
S 22/S 23	
1960	

from which

A fir, 35 ins. diam., bears N. 87° E., 60 lks. dist.,
mkd. S $1/16$ S23 BT.

A fir 28 ins. diam., bears N. 14° W., 75 lks. dist.,
mkd. S $1/16$ S22 BT.

Descend 248 ft. over broken NW. slope.