

County Surveyor's Record, Douglas County, Oregon

-3-

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 11 W.

CHAINS		
25.55	Enter creek bottom, edge bears N. 80° E. and S. 80° W.; desc. 4 ft. over gentle N. slope.	
26.75	Branch, 6 lks. wide, course S. 80° W.; asc. 110 ft. over SE. slope.	
29.85	Dirt access road, 20 lks. wide, bears N. 80° E. and S. 80° W.	
34.10	Spur, slopes S. 25° E.; desc. 48 ft. along E. slope.	
37.45	Ravine, course S. 85° E.; Asc. 37 ft. over SE. slope.	
40.30	<p data-bbox="337 778 1442 848">The $\frac{1}{4}$ Sec. Cor. of secs. 22 and 23, determined at record bearing and distance from each of the original bearing trees;</p> <p data-bbox="410 862 1442 931">A fir, 50 ins. diam., bears N. 77° E., 10 lks. dist., with no marks remaining on scaled off bark blaze.</p> <p data-bbox="410 959 1442 1028">A sawed fir stump, 53 ins. diam., bears S. 34$\frac{1}{2}$° W., 36 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on bark.</p> <p data-bbox="345 1083 651 1125">At the corner point</p> <p data-bbox="345 1153 1442 1222">Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap mkd.</p> <p data-bbox="760 1250 976 1374" style="text-align: center;"> $\frac{1}{4}$ S 22/S 23 T 21 S R 11 W 1961 </p> <p data-bbox="345 1402 505 1444">from which</p> <p data-bbox="410 1471 1442 1568">A fir 50 ins. diam., bears N. 77° E., 10 lks. dist., mkd. $\frac{1}{4}$ S23 BT. (This is the original NE. tree, remarked because no other tree is available).</p> <p data-bbox="410 1596 1442 1665">An alder, 18 ins. diam., bears N. 29° W., 75 lks. dist., marked $\frac{1}{4}$ S22 BT.</p> <hr data-bbox="708 1679 1097 1693"/> <p data-bbox="345 1721 976 1762">N. 5° 50' W., beginning new measurement.</p> <p data-bbox="345 1790 821 1832">Descent 16 ft. along E. slope.</p> <p data-bbox="209 1860 305 1882">2.85</p>	Ravine, course S. 20° E.; asc. 259 ft. over general S. slope.
9.85	Spur, slopes S. 50° W.; asc. 28 ft. over SW. slope.	
13.25	Top of ascent, slopes W.; desc. 35 ft. along W. slope.	
15.90	Ravine, course W.; asc. 116 ft. over S. slope.	
19.95	<p data-bbox="337 2137 1442 2178">Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p data-bbox="337 2206 1442 2275">Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in ground, with brass cap mkd.</p> <p data-bbox="808 2303 959 2428" style="text-align: center;"> N 1/16 S 22/S 23 1960 </p> <p data-bbox="337 2455 496 2497">from which</p> <p data-bbox="410 2525 1442 2622">A fir, 15 ins. diam., bears N. 45° E., 54 lks. dist., mks. N 1/16 S23 BT.</p> <p data-bbox="410 2650 1442 2719">A Maple, 18 ins. diam., bears S. 63° W., 12 lks. dist. mkd. N 1/16 S22 BT.</p>	