

County Surveyor's Record, Douglas County, Oregon

-5-

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 11 W.

CHAINS	
40.16	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 12 ins. long, 1 in. diam., 6 ins. in drill hole, in sandstone ledge, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 14 $\frac{1}{4}$ S 23 T 21 S R 11 W 1960 </p> <p>from which</p> <p>A cedar, 12 ins. diam., bears N. $44\frac{1}{2}^\circ$ W., 12 lks. dist., mkd. $\frac{1}{4}$ S14 BT.</p> <p>A fir, 18 ins. diam., bears S. $73\frac{1}{2}^\circ$ E., 21 lks. dist., mkd. $\frac{1}{4}$ S23 BT.</p> <p>Descent 70 ft. over W. slope.</p>
41.10	Branch, 4 lks. wide, course S. 15° E.; asc. 350 ft. over E. slope.
48.65	Spur, slopes NE.; desc. 89 ft. along N. slope.
54.45	Ravine, course N.; asc. 248 ft. over broken E. slope.
59.90	Spur ridge, bears N. 20° E. and S. 30° W.; desc. 21 ft. along N. slope.
66.40	Ridge, divide between Otter Creek and Brainard Creek, bears N. 30° W. and S. 30° E.; desc. 480 ft. over broken W. slope, changing to NW. slope.
72.20	Ravine, course N. 60° W.; asc. 80 ft. over SE. slope.
76.15	Spur, slopes S.; desc. 145 ft. over W. slope.
79.55	Ravine, course S. 30° W.; asc. 26 ft. over SE. slope.
80.32	The cor. of secs. 14, 15, 22, and 23.
	Land, mountainous.
	Soil, sandy clay loam
Timber,	fir, cedar, hemlock, maple, alder, dogwood, madrona, and chinquapin; undergrowth, vine maple, coast huckleberry, arrowwood, hazel, red huckleberry, salmonberry, salal, and fern.
	N. $0^\circ 17'$ E., bet. secs. 14 and 15.
	Ascend 231 ft. over general S. slope, through heavy timber and dense undergrowth.
9.75	Spur, slopes W.; desc. 390 ft. over general N. slope.
15.95	Ravine, course N. 80° W.; asc. 140 ft. over general S. slope.
19.845	Point for the S $1/16$ sec. cor. of secs. 14 and 15.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	S $1/16$ S 15/S 14 1960
	from which
	A fir, 11 ins. diam., bears S. $59\frac{1}{2}^\circ$ E., 38 lks. dist., mkd. S $1/16$ S14 BT.