

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 11 W.

CHAINS													
	A fir, 20 ins. diam., bears S. 78° W., 38 lks. dist., mkd. S 1/16 S15 BT.												
	Ascend 292 ft. over broken SW. slope.												
34.50	Ridge, bears NW. and S. 55° E.; desc. 191 ft. over NE. slope.												
38.45	Ravine, course N. 70° E.; asc. 69 ft. over SE. slope.												
39.69	Point for the 1/4 corner of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.												
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	FD. OK PER WOBBE M104-43A&B MAY 87												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">S 15</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="padding: 0 5px;">T 21</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">R 11</td> </tr> <tr> <td colspan="3" style="text-align: center;">W</td> </tr> <tr> <td colspan="3" style="text-align: center;">1960</td> </tr> </table>	S 15		S 14	T 21	S	R 11	W			1960		
S 15		S 14											
T 21	S	R 11											
W													
1960													
	from which												
	A maple, 23 ins. diam., bears S. 88° E., 64 lks. dist., mkd. 1/4 S14 BT.												
	A maple, 35 ins. diam., bears S. 29 1/2° W., 59 lks. dist., mkd. 1/4 S15 BT.												
	Ascent 125 ft. over SE. slope.												
42.35	Spur, slopes N. 80° E.; desc. 180 ft. over NE. slope.												
47.60	Ravine, course S. 65° E.; asc. 227 ft. over general S. slope.												
52.30	Spur, slopes N. 65° E.; desc. 327 ft. over general N. slope.												
60.00	Ravine, course N. 65° E.; asc. 68 ft. over SE. slope.												
65.00	Spur, slopes E.; desc. 60 ft. over NE. slope.												
67.95	Ravine, course S. 65° E., asc. 224 ft. over broken SE. slope.												
73.15	Spur, slopes E.; desc. 226 ft. over N. slope, changing to NE. slope.												
79.38	The cor. of secs. 10, 11, 14, and 15, determined from the remains of the original bearing trees;												
	FD OK PER WOBBE M104-43A&B MAY '87												
	A turned out fir, 38 ins. diam., bears S. 87° E., 235 lks. dist., with scribe mark S visible on partly opened blaze. (Record distance, 212 lks.)												
	A sawed fir stump, 38 ins. diam., bears S. 43° W., 30 lks. dist., with no marks remaining on bottom of scaled bark blaze.												
	A turned out fir, 35 ins. diam., bears N. 2° W., 146 lks. dist., with no marks remaining. (Record dist. 158 lks.)												
	There is no remaining evidence of the other original bearing tree or of the original corner tree.												
	At corner point												
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.												
	FD. OK. M 111-10 11/90												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="3" style="padding: 0 5px;">T 21 S R 11 W</td> </tr> <tr> <td style="padding: 0 5px;">S 10</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 11</td> </tr> <tr> <td style="padding: 0 5px;">S 15</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td colspan="3" style="text-align: center;">1960</td> </tr> </table>	T 21 S R 11 W			S 10		S 11	S 15		S 14	1960		
T 21 S R 11 W													
S 10		S 11											
S 15		S 14											
1960													