

County Surveyor's Record, Douglas County, Oregon

-7-

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 11 W.

CHAINS

from which new bearing trees:

A cedar, 15 ins. diam., bears N. $65\frac{3}{4}^{\circ}$ E., 16 lks. dist.,
mkd. T21S R11W S11 BT.

A hemlock, 25 ins. diam., bears S. $33\frac{1}{4}^{\circ}$ E., 12 lks. dist.,
mkd. T21S R11W S14 BT.

A cedar, 18 ins. diam., bears S. $76\frac{3}{4}^{\circ}$ W., 24 lks. dist.,
mkd. T21S R11W S15 BT.

A cedar, 16 ins. diam., bears N. $39\frac{1}{2}^{\circ}$ W., 29 lks. dist.,
mkd. T21S R11W S10 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, cedar, hemlock, alder, maple, madrone, and chinquapin;
undergrowth, vine maple, salmonberry, coast huckleberry, young
timber, salal, red huckleberry, arrowwood, hazel, ceanothus, and
fern.

At point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, established at
record bearing and distance from the record witness corner for
the $\frac{1}{4}$ sec. cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins in the
ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \uparrow \\ \text{S } 28 \text{ | S } 27 \\ \text{T } 21 \text{ S } \text{ | R } 11 \text{ W} \\ 1960 \end{array}$$

from which

A cedar 38 ins. diam., bears N. $37\frac{1}{2}^{\circ}$ E., 172 lks. dist.,
mkd. $\frac{1}{4}$ S27 BT.

A cedar 12 ins. diam., bears N. 44° W., 66 lks. dist.,
mkd. $\frac{1}{4}$ S28 BT.

Corner is 30 lks. west of ravine, course N. 10° E.

From this point the record witness cor. for the $\frac{1}{4}$ sec. cor. bears
West, 3.21 chs. dist., determined at record bearing from the
remains of the original bearing trees:

A fir snag, 72 ins. diam., bears N. $58\frac{1}{2}^{\circ}$ E., 7 lks. dist.,
with scribe mark 4 visible on bark blaze.
(Record distance, 2 lks.)

A fir snag, 35 ins. diam., bears S. $82\frac{1}{2}^{\circ}$ W., 15 lks. dist.,
with no marks remaining on bark blaze.
(Record distance, 12 lks.)

and two bearing trees of which I have no record:

A fir, 25 ins. diam., bears S. $44\frac{1}{4}^{\circ}$ E., 5 lks. dist.,
with healed double blaze. I open and uncover scribe
mark S.

A fir, 18 ins. diam., bears S. 18° W., 36 lks. dist.,
with healed double blaze.

At the corner point, which is on top of spur, slopes N.