

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 11 W.

CHAINS	<p>A fir, 23 ins. diam., bears S. $80\frac{1}{2}^\circ$ W., 85 lks. dist., mkd. $\frac{1}{4}$ S27 BT.</p> <p>Reset the iron pipe alongside the iron post.</p> <hr/> <p>N. $87^\circ 38'$ W., beginning new measurement.</p> <p>Ascend 80 ft. over SE. slope.</p> <p>5.00 Spur, slopes S. 30° E.; desc. 75 ft. over SW. slope.</p> <p>12.00 Ravine, course S. 30° E.; asc. 300 ft. over broken E. slope.</p> <p>18.80 Spur, slopes S.; desc. 18 ft. over W. slope.</p> <p>19.72 Point for the W $1/16$ sec. cor. of secs. 22 and 27.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W $1/16$ $\frac{S 22}{S 27}$ 1960</p> </div> <p>from which</p> <p>A fir, 10 ins. diam. bears N. 52° E., 35 lks. dist., mkd. W $1/16$ S22 BT.</p> <p>A fir, 12 ins. diam., bears S. 15° E., 63 lks. dist., mkd. W $1/16$ S27 BT.</p> <p>Descend 40 ft. over SW. slope.</p> <p>22.00 Ravine, course S.; asc. 80 ft. over SE. slope.</p> <p>28.00 Spur, slopes S. 10° W.; desc. 250 ft. over general W. slope.</p> <p>39.44 The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, dogwood, chinquapin, and madrona; undergrowth, vine maple, salmonberry, coast huckleberry, red huckleberry, black berry, hazel, arrowwood, ceanothus, salal, and fern.</p> <hr/> <p>N. $2^\circ 34'$ W., bet. secs. 21 and 22.</p> <p>Descend 61 ft. along W. slope, through heavy timber and dense undergrowth.</p> <p>8.00 Ravine, course S. 15° W.; asc. 314 ft. over broken SE. slope.</p> <p>19.14 Point for the S $1/16$ sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S $1/16$ S 21/S 22 1960</p> </div> <p>from which</p> <p>A fir, 53 ins. diam., bears S. $37\frac{1}{4}^\circ$ E., 67 lks. dist., mkd. S $1/16$ S22 BT.</p> <p>A hemlock, 15 ins. diam., bears N. 81° W., 117 lks. dist., mkd. S $1/16$ S21 BT.</p>
--------	---

*FD 2/84
S. PROCHNAU
1966-11-18*